

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



VCO Product Specification

Model: VCO-215TC **Rev:** A **Date:** 12/1/2003

Customer:

Operating Temperature Range: (-55 ° to 100 ° C)

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	2500		4000	MHz	X	
Tuning Voltage:						
2500 MHz	0	1.1		Vdc	X	
4000 MHz		13.5	20	Vdc	X	
Tuning Sensitivity:						
2500 MHz	82.5	110	137.5	MHz/V	X	Typical Linearity 2.3:1
2875 MHz	93.75	125	156.25	MHz/V	X	
3250 MHz	120	160	200	MHz/V	X	
3625 MHz	93.75	125	156.25	MHz/V	X	
4000 MHz	56.25	75	93.75	MHz/V	X	
Output Power -	-2.5	0.5	3.5	dBm	X	
Output Phase Noise:						
10 kHz		-84	-78	dBc/Hz	X	
100 kHz		-106	-100	dBc/Hz	X	
1000 kHz		-126	-120	dBc/Hz	X	
Power Supply -	14.5	15	15.5	Volts		
Supply Current -		19	23	mA	X	
Harmonic Suppression:						
2nd Harmonic		-30	-10	dBc	X	
3rd Harmonic		-25	-10	dBc	X	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 14.5 to 15.5 Volts		2	4	MHz p-p		
Frequency Pulling - 12 dBRL		10	16	MHz p-p		
Tuning Port Capacitance -		27		pF		
Output Impedance -		50		Ω		
Modulation:						
Bandwidth	15000	25000		kHz		Zg=50 Ohms

Package Information

Package Type:	SMT-2	Drawing Number:	A21959
Dimensions:	0.45 x 0.45 x 0.17 inches	Drawing Revision:	B

Comments

X Indicates parameter to be tested 100% in production

ALSO AVAILABLE IN TO-8 PACKAGE

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza Microdevices' products are subject to change without notice. Buyers should consult Sirenza Microdevices' standard terms and conditions of sale for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any product for use in life-support devices and/or systems.