

阅读申明

1. 本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
2. 本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
3. 本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
4. 如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。



Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets".

HiPerFRED™ Epitaxial Diode with common cathode and soft recovery

I_{FAV} = 2x15 A
V_{RRM} = 200 V
t_{rr} = 25 ns

V _{RSM} V	V _{RRM} V	Type
200	200	DSEC 29-02AS



Symbol	Conditions	Maximum Ratings	
I _{FRMS}		35	A
I _{FAVM}	T _C = 150°C; rectangular, d = 0.5	15	A
I _{FSM}	T _{VJ} = 45°C; t _p = 10 ms (50 Hz), sine	140	A
E _{AS}	T _{VJ} = 25°C; non-repetitive I _{AS} = 2.5 A; L = 180 µH	0.8	mJ
I _{AR}	V _A = 1.5·V _R typ.; f = 10 kHz; repetitive	0.3	A
T _{VJ}		-55...+175	°C
T _{VJM}		175	°C
T _{stg}		-55...+150	°C
P _{tot}	T _C = 25°C	95	W
M _d	mounting torque	0.45...0.55 4...5	Nm lb.in.
Weight	typical	2	g

Symbol	Conditions	Characteristic Values	
		typ.	max.
I _R ①	T _{VJ} = 25°C; V _R = V _{RRM} T _{VJ} = 150°C; V _R = V _{RRM}	100 0.5	µA mA
V _F ②	I _F = 15 A; T _{VJ} = 150°C T _{VJ} = 25°C	0.86 1.06	V
R _{thJC} R _{thCH}		0.5	1.6 K/W K/W
t _{rr}	I _F = 1 A; -di/dt = 100 A/µs; V _R = 30 V; T _{VJ} = 25°C	25	ns
I _{RM}	V _R = 100 V; I _F = 25 A; -di _F /dt = 100 A/µs T _{VJ} = 100°C	3.5	4.4 A

Pulse test: ① Pulse Width = 5 ms, Duty Cycle < 2.0 %
② Pulse Width = 300 µs, Duty Cycle < 2.0 %

Data according to IEC 60747 and per diode unless otherwise specified.

Recommended replacement:
DPG 30C200PC




Fig. 1 Forward current I_F versus V_F




Fig. 2 Typ. reverse recovery charge Q_r




Fig. 3 Typ. peak reverse current I_{RM}




Fig. 4 Typ. dynamic parameters Q_r , I_{RM}




Fig. 5 Typ. recovery time t_{rr} versus $-di_F/dt$




Fig. 6 Typ. peak forward voltage V_{FR} and t_{fr}




Fig. 7 Transient thermal resistance junction to case

Constants for Z_{thJC} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.851	0.0052
2	0.328	0.0003
4	0.421	0.0409