

阅读申明


1. 本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
2. 本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
3. 本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
4. 如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets".

50Amp Schottky Rectifier

FST5080 — FST50100



Similar to TO-247AD

Dim.	Inches		Millimeter		Notes
	Minimum	Maximum	Minimum	Maximum	
A	.185	.209	4.70	5.31	
B	.087	.102	2.21	2.59	
C	.059	.098	1.50	2.49	
D	.040	.055	1.02	1.40	
E	.079	.094	2.01	2.39	
F	.118	.133	3.00	3.38	
G	.016	.031	.410	0.78	
H	.819	.883	20.80	22.4	
J	.627	.650	15.93	16.5	
K	.215	—	5.46	—	Typ.
L	.790	.810	20.07	20.6	
M	.157	.180	3.99	4.57	
N	.139	.144	3.53	3.66	Dia.
P	.255	.300	6.48	7.62	
Q	.170	.210	4.32	5.33	
R	.080	.110	2.03	2.79	

Microsemi Catalog Number

Industry Part Number

Repetitive Peak Reverse Voltage

Transient Peak Reverse Voltage

FST5080

40CPQ080
MBR4080WT
MBR5080WT

80V

80V

FST5090

90V

90V

FST50100

40CPQ100
63CPQ100
MBR40100WT
MBR50100WT

100V

100V

- Guard ring for reverse protection
- Low power loss, high efficiency
- High surge capacity
- 175°C Junction Temperature
- VRRM 80 to 100 Volts

Electrical Characteristics

Average Forward Current per pkg.

$I_{F(AV)}$ 50 Amps

$T_C = 129^\circ\text{C}$, Square wave, $R_{\theta JC} = 1.0^\circ\text{C}/\text{W}$

Average Forward Current per leg

$I_{F(AV)}$ 25 Amps

$T_C = 129^\circ\text{C}$, Square wave, $R_{\theta JC} = 2.0^\circ\text{C}/\text{W}$

Maximum Surge Current per leg

I_{FSM} 400 Amps

8.3ms, half sine, $T_J = 175^\circ\text{C}$

Max. Peak Forward Voltage per leg

V_{FM} .62 Volts

$I_{FM} = 25\text{A}$, $T_J = 175^\circ\text{C}^*$

Max. Peak Forward Voltage per leg

V_{FM} .85 Volts

$I_{FM} = 25\text{A}$, $T_J = 25^\circ\text{C}^*$

Max. Peak Reverse Current per leg

I_{RM} 15 mA

V_{RRM} , $T_J = 125^\circ\text{C}^*$

Max. Peak Reverse Current per leg

I_{RM} 500 μA

V_{RRM} , $T_J = 25^\circ\text{C}$

Typical Junction Capacitance per leg

C_J 920 pF

$VR = 5.0\text{V}$, $T_J = 25^\circ\text{C}$

*Pulse test: Pulse width 300 usec. Duty Cycle 2%

Thermal and Mechanical Characteristics

Storage temp range

T_{SG}

-55°C to +175°C

Operating junction temp range

T_J

-55°C to +175°C

Max thermal resistance per leg

R_{θJC}

2.0°C/W

Max thermal resistance per pkg.

R_{θJC}

1.0°C/W

Mounting Torque

5-10 inch pounds (#6 screw)

Weight

.22 ounces (6.36 grams) typical

FST5080 – FST50100

Figure 1
Typical Forward Characteristics – Per Leg




Figure 2
Typical Reverse Characteristics – Per Leg




Figure 3
Typical Junction Capacitance – Per Leg




Figure 4
Forward Current Derating – Per Leg




Figure 5
Maximum Forward Power Dissipation – Per Leg

