

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

High-voltage Switching Transistor

(Camera strobes and Telephone, Power supply) (−400V, −0.1A)

2SA1759

● Features

- 1) High breakdown voltage. ($V_{CE0} = -400V$)
- 2) Low saturation voltage, typically $V_{CE(sat)} = -0.2V$ at $I_C / I_E = -20mA / -2mA$.
- 3) High switching speed, typically $t_f = 1 \mu s$ at $I_C = 100mA$.
- 4) Wide SOA (safe operating area).
- 5) Complements the 2SA4505.

● Packaging specifications and hFE

Type	2SA1759
Package	MPT3
hFE	P
Marking	AH*
Code	T100
Basic ordering unit (pieces)	3000

* Denotes hFE

● Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV_{CBO}	−400	—	—	V	$I_C = -50 \mu A$
Collector-emitter breakdown voltage	BV_{CEO}	−400	—	—	V	$I_C = -1mA$
Emitter-base breakdown voltage	BV_{EBO}	−7	—	—	V	$I_E = -50 \mu A$
Collector cutoff current	I_{CBO}	—	—	−10	μA	$V_{CB} = -400V$
Emitter cutoff current	I_{EBO}	—	—	−10	μA	$V_{EB} = -6V$
Collector-emitter saturation voltage	$V_{CE(sat)}$	—	−0.2	−0.5	V	$I_C / I_E = -20mA / -2mA$
Base-emitter saturation voltage	$V_{BE(sat)}$	—	—	−1.2	V	$I_C / I_E = -20mA / -2mA$
DC current transfer ratio	hFE	82	—	180	—	$V_{CE} = -10V, I_C = -10mA$
Transition frequency	fT	—	12	—	MHz	$V_{CE} = -10V, I_E = 10mA, f = 5MHz$
Output capacitance	Cob	—	13	—	pF	$V_{CB} = -10V, I_E = 0A, f = 1MHz$
Turn-on time	t _{on}	—	0.7	—	μs	$I_C = -100mA, R_L = 1.5k\Omega$
Storage time	t _{stg}	—	1.8	—	μs	$I_{B1} = -I_{B2} = -10mA$
Fall time	t _f	—	1	—	μs	$V_{CC} \sim -150V$

(96-97-A324)

Power Transistor (400V, 0.1A)

2SC4505 / 2SC4620

● Features

- 1) High breakdown voltage. ($V_{CE0} = 400V$)
- 2) Low saturation voltage, typically $V_{CE(sat)} = 0.05V$ at $I_C / I_E = 10mA / 1mA$.
- 3) High switching speed, typically $t_f = 1.7 \mu s$ at $I_C = 100mA$.
- 4) Complements the 2SC4505 and the 2SA1759.

● Packaging specifications and hFE

Type	2SC4505	2SC4620
Package	MPT3	ATV
hFE	PQ	Q
Marking	CE*	—
Code	T100	TV2
Basic ordering unit (pieces)	1000	2500

* Denotes hFE

● Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV_{CBO}	400	—	—	V	$I_C = 50 \mu A$
Collector-emitter breakdown voltage	BV_{CEO}	400	—	—	V	$I_C = 1mA$
Emitter-base breakdown voltage	BV_{EBO}	7	—	—	V	$I_E = 50 \mu A$
Collector cutoff current	I_{CBO}	—	—	10	μA	$V_{CB} = 400V$
Emitter cutoff current	I_{EBO}	—	—	10	μA	$V_{EB} = 6V$
Collector-emitter saturation voltage	$V_{CE(sat)}$	—	0.05	0.5	V	$I_C = 10mA, I_E = 1mA$
Base-emitter saturation voltage	$V_{BE(sat)}$	—	—	1.5	V	$I_C = 10mA, I_E = 1mA$
DC current transfer ratio	hFE	82	—	270	—	$V_{CE} / I_C = 10V / 10mA$
Transition frequency	fT	—	20	—	MHz	$V_{CE} = 10V, I_E = -10mA, f = 10MHz$
Output capacitance	Cob	—	7	—	pF	$V_{CB} = 10V, I_E = 0A, f = 1MHz$
Turn-on time	t _{on}	—	1	—	μs	$I_C = 100mA$
Storage time	t _{stg}	—	5.5	—	μs	$I_{B1} = -I_{B2} = 10mA$
Fall time	t _f	—	1.7	—	μs	$V_{CC} \sim -150V$

(96-178-C300)

● Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-base voltage	V_{CBO}	−400	V
Collector-emitter voltage	V_{CEO}	−400	V
Emitter-base voltage	V_{EBO}	−7	V
Collector current	I_C	−0.1	A (DC)
		−0.2	A (Pulse) *1
Collector power dissipation	P_C	0.5	W
		2 *2	
Junction temperature	Tj	150	°C
Storage temperature	Tstg	−55~+150	°C

*1 Single pulse, Pw=100ms

*2 When mounted on a 40×40×0.7 mm ceramic board.

● Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Collector-base voltage	V_{CBO}	400	V
Collector-emitter voltage	V_{CEO}	400	V
Emitter-base voltage	V_{EBO}	7	V
Collector current	I_C	0.1	A
		0.2	A *
Collector power dissipation	P_C	0.5	W
		1	
Junction temperature	Tj	150	°C
Storage temperature	Tstg	−55~+150	°C

* Single pulse Pw=20ms Duty=1 / 2