

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

# BC546B, BC547A, B, C, BC548B, C

## Amplifier Transistors

### NPN Silicon

#### Features

- Pb-Free Packages are Available\*

#### MAXIMUM RATINGS

| Rating   | Symbol         | Value          | Unit                       |
|--|----------------|----------------|----------------------------|
| Collector - Emitter Voltage<br>BC546<br>BC547<br>BC548                                 | $V_{CEO}$      | 65<br>45<br>30 | Vdc                        |
| Collector - Base Voltage<br>BC546<br>BC547<br>BC548                                    | $V_{CBO}$      | 80<br>50<br>30 | Vdc                        |
| Emitter - Base Voltage   | $V_{EBO}$      | 6.0            | Vdc                        |
| Collector Current - Continuous   | $I_C$          | 100            | mAdc                       |
| Total Device Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 625<br>5.0     | mW<br>mW/ $^\circ\text{C}$ |
| Total Device Dissipation @ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 1.5<br>12      | W<br>mW/ $^\circ\text{C}$  |
| Operating and Storage Junction<br>Temperature Range                                    | $T_J, T_{stg}$ | -55 to +150    | $^\circ\text{C}$           |

#### THERMAL CHARACTERISTICS

| Characteristic                             | Symbol          | Max  | Unit                      |
|--|-----------------|------|---------------------------|
| Thermal Resistance,<br>Junction-to-Ambient | $R_{\theta JA}$ | 200  | $^\circ\text{C}/\text{W}$ |
| Thermal Resistance,<br>Junction-to-Case    | $R_{\theta JC}$ | 83.3 | $^\circ\text{C}/\text{W}$ |



Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.




ON Semiconductor®

<http://onsemi.com>



TO-92  
CASE 29  
STYLE 17

#### MARKING DIAGRAM



BC54x = Device Code  
x = 6, 7, or 8  
A = Assembly Location  
Y = Year  
WW = Work Week  
■ = Pb-Free Package

(Note: Microdot may be in either location)

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

# BC546B, BC547A, B, C, BC548B, C

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise noted)

| Characteristic  | Symbol   | Min                  | Typ                                    | Max                              | Unit                                   |                  |
|---|--|----------------------|--|----------------------------------|--|------------------|
| <b>OFF CHARACTERISTICS</b>  |  |                      |  |                                  |  |                  |
| Collector – Emitter Breakdown Voltage<br>(I <sub>C</sub> = 1.0 mA, I <sub>B</sub> = 0)  | BC546<br>BC547<br>BC548  | V <sub>(BR)CEO</sub> | 65<br>45<br>30                         | –<br>–<br>–                      | –<br>–<br>–                            | V                |
| Collector – Base Breakdown Voltage<br>(I <sub>C</sub> = 100 μA <sub>dc</sub> )  | BC546<br>BC547<br>BC548  | V <sub>(BR)CBO</sub> | 80<br>50<br>30                         | –<br>–<br>–                      | –<br>–<br>–                            | V                |
| Emitter – Base Breakdown Voltage<br>(I <sub>E</sub> = 10 μA, I <sub>C</sub> = 0)  | BC546<br>BC547<br>BC548  | V <sub>(BR)EBO</sub> | 6.0<br>6.0<br>6.0                      | –<br>–<br>–                      | –<br>–<br>–                            | V                |
| Collector Cutoff Current<br>(V <sub>CE</sub> = 70 V, V <sub>BE</sub> = 0)<br>(V <sub>CE</sub> = 50 V, V <sub>BE</sub> = 0)<br>(V <sub>CE</sub> = 35 V, V <sub>BE</sub> = 0)<br>(V <sub>CE</sub> = 30 V, T <sub>A</sub> = 125°C) | BC546<br>BC547<br>BC548<br>BC546/547/548                               | I <sub>CES</sub>     | –<br>–<br>–<br>–                       | 0.2<br>0.2<br>0.2<br>–           | 15<br>15<br>15<br>4.0                  | nA<br><br><br>μA |
| <b>ON CHARACTERISTICS</b>   |  |                      |  |                                  |  |                  |
| DC Current Gain<br>(I <sub>C</sub> = 10 μA, V <sub>CE</sub> = 5.0 V)  | BC547A<br>BC546B/547B/548B<br>BC548C                                   | h <sub>FE</sub>      | –<br>–<br>–                            | 90<br>150<br>270                 | –<br>–<br>–                            | –                |
| (I <sub>C</sub> = 2.0 mA, V <sub>CE</sub> = 5.0 V)  | BC546<br>BC547<br>BC548<br>BC547A<br>BC546B/547B/548B<br>BC547C/BC548C |                      | 110<br>110<br>110<br>110<br>200<br>420 | –<br>–<br>–<br>180<br>290<br>520 | 450<br>800<br>800<br>220<br>450<br>800 |                  |
| (I <sub>C</sub> = 100 mA, V <sub>CE</sub> = 5.0 V)  | BC547A/548A<br>BC546B/547B/548B<br>BC548C                              |                      | –<br>–<br>–                            | 120<br>180<br>300                | –<br>–<br>–                            |                  |
| Collector – Emitter Saturation Voltage<br>(I <sub>C</sub> = 10 mA, I <sub>B</sub> = 0.5 mA)<br>(I <sub>C</sub> = 100 mA, I <sub>B</sub> = 5.0 mA)<br>(I <sub>C</sub> = 10 mA, I <sub>B</sub> = See Note 1)                      |  | V <sub>CE(sat)</sub> | –<br>–<br>–                            | 0.09<br>0.2<br>0.3               | 0.25<br>0.6<br>0.6                     | V                |
| Base – Emitter Saturation Voltage<br>(I <sub>C</sub> = 10 mA, I <sub>B</sub> = 0.5 mA)  |  | V <sub>BE(sat)</sub> | –                                      | 0.7                              | –                                      | V                |
| Base – Emitter On Voltage<br>(I <sub>C</sub> = 2.0 mA, V <sub>CE</sub> = 5.0 V)<br>(I <sub>C</sub> = 10 mA, V <sub>CE</sub> = 5.0 V)  |  | V <sub>BE(on)</sub>  | 0.55<br>–                              | –<br>–                           | 0.7<br>0.77                            | V                |
| <b>SMALL-SIGNAL CHARACTERISTICS</b>   |  |                      |  |                                  |  |                  |
| Current – Gain – Bandwidth Product<br>(I <sub>C</sub> = 10 mA, V <sub>CE</sub> = 5.0 V, f = 100 MHz)  | BC546<br>BC547<br>BC548  | f <sub>T</sub>       | 150<br>150<br>150                      | 300<br>300<br>300                | –<br>–<br>–                            | MHz              |
| Output Capacitance<br>(V <sub>CB</sub> = 10 V, I <sub>C</sub> = 0, f = 1.0 MHz)   |  | C <sub>obo</sub>     | –                                      | 1.7                              | 4.5                                    | pF               |
| Input Capacitance<br>(V <sub>EB</sub> = 0.5 V, I <sub>C</sub> = 0, f = 1.0 MHz)   |  | C <sub>ibo</sub>     | –                                      | 10                               | –                                      | pF               |
| Small – Signal Current Gain<br>(I <sub>C</sub> = 2.0 mA, V <sub>CE</sub> = 5.0 V, f = 1.0 kHz)  | BC546<br>BC547/548<br>BC547A<br>BC546B/547B/548B<br>BC547C/548C        | h <sub>fe</sub>      | 125<br>125<br>125<br>240<br>450        | –<br>–<br>220<br>330<br>600      | 500<br>900<br>260<br>500<br>900        | –                |
| Noise Figure<br>(I <sub>C</sub> = 0.2 mA, V <sub>CE</sub> = 5.0 V, R <sub>S</sub> = 2 kΩ,<br>f = 1.0 kHz, Δf = 200 Hz)  | BC546<br>BC547<br>BC548  | NF                   | –<br>–<br>–                            | 2.0<br>2.0<br>2.0                | 10<br>10<br>10                         | dB               |

1. I<sub>B</sub> is value for which I<sub>C</sub> = 11 mA at V<sub>CE</sub> = 1.0 V.

# BC546B, BC547A, B, C, BC548B, C

## BC547/BC548




Figure 1. Normalized DC Current Gain




Figure 2. "Saturation" and "On" Voltages




Figure 3. Collector Saturation Region




Figure 4. Base-Emitter Temperature Coefficient




Figure 5. Capacitances




Figure 6. Current-Gain - Bandwidth Product

# BC546B, BC547A, B, C, BC548B, C

## BC546




Figure 7. DC Current Gain




Figure 8. "On" Voltage




Figure 9. Collector Saturation Region




Figure 10. Base-Emitter Temperature Coefficient




Figure 11. Capacitance




Figure 12. Current-Gain - Bandwidth Product

## BC546B, BC547A, B, C, BC548B, C

### DEVICE ORDERING INFORMATION



| Device     | Package            | Shipping†          |
|------------|--------------------|--------------------|
| BC546B     | TO-92              | 5000 Units / Bulk  |
| BC546BG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC546BRL1  | TO-92              | 2000 / Tape & Reel |
| BC546BRL1G | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC546BZL1  | TO-92              | 2000 / Ammo Box    |
| BC546BZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC547ARL   | TO-92              | 2000 / Tape & Reel |
| BC547ARLG  | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC547ARL1  | TO-92              | 2000 / Tape & Reel |
| BC547ARL1G | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC547AZL1  | TO-92              | 2000 / Ammo Box    |
| BC547AZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC547B     | TO-92              | 5000 Units / Bulk  |
| BC547BG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC547BRL1  | TO-92              | 2000 / Tape & Reel |
| BC547BRL1G | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC547BZL1  | TO-92              | 2000 / Ammo Box    |
| BC547BZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC547C     | TO-92              | 5000 Units / Bulk  |
| BC547CG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC547CZL1  | TO-92              | 2000 / Ammo Box    |
| BC547CZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC548B     | TO-92              | 5000 Units / Bulk  |
| BC548BG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC548BRL1  | TO-92              | 2000 / Tape & Reel |
| BC548BRL1G | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC548BZL1  | TO-92              | 2000 / Ammo Box    |
| BC548BZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC548C     | TO-92              | 5000 Units / Bulk  |
| BC548CG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC548CZL1  | TO-92              | 2000 / Ammo Box    |
| BC548CZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# BC546B, BC547A, B, C, BC548B, C

## PACKAGE DIMENSIONS

TO-92 (TO-226)  
CASE 29-11  
ISSUE AL



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.175  | 0.205 | 4.45        | 5.20  |
| B   | 0.170  | 0.210 | 4.32        | 5.33  |
| C   | 0.125  | 0.165 | 3.18        | 4.19  |
| D   | 0.016  | 0.021 | 0.407       | 0.533 |
| G   | 0.045  | 0.055 | 1.15        | 1.39  |
| H   | 0.095  | 0.105 | 2.42        | 2.66  |
| J   | 0.015  | 0.020 | 0.39        | 0.50  |
| K   | 0.500  | ---   | 12.70       | ---   |
| L   | 0.250  | ---   | 6.35        | ---   |
| N   | 0.080  | 0.105 | 2.04        | 2.66  |
| P   | ---    | 0.100 | ---         | 2.54  |
| R   | 0.115  | ---   | 2.93        | ---   |
| V   | 0.135  | ---   | 3.43        | ---   |

### STYLE 17:

1. COLLECTOR
2. BASE
3. EMITTER

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85062-1312 USA  
**Phone:** 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
**Email:** orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free USA/Canada

**Japan:** ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
**Phone:** 81-3-5773-3850

**ON Semiconductor Website:** <http://onsemi.com>

**Order Literature:** <http://www.onsemi.com/litorder>

For additional information, please contact your local Sales Representative.