

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



## Tflex™ XS400 Series Gap Filler Material

Compliant 2.0 W/mK Thermally Conductive Gap Filler

[Stock Locator](#)

Tflex™ XS400 is a compliant elastomer gap filler designed to provide moderate thermal performance. This soft interface pad conforms well with minimal pressure, resulting in little or no stress on mating parts. Tflex™ XS400 is naturally tacky, no adhesive coating is required. Due to its TG liner on the other side, Tflex™ XS400 is electrically insulating, stable from -40°C to 160°C and is certified to UL 94V0 flammability rating.

Results 1 - 19 of 19

Item #	Color	Thickness	Hardness	Outgassing TML	Outgassing CVCM
Tflex XS420	Dark Grey / Red Liner	0.020 inches 0.508 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS430	Dark Grey / Red Liner	0.030 inches 0.762 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS440	Dark Grey / Red Liner	0.040 inches 1.02 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS450	Dark Grey / Red Liner	0.050 inches 1.27 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS460	Dark Grey / Red Liner	0.060 inches 1.52 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS470	Dark Grey / Red Liner	0.070 inches 1.78 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS480	Dark Grey / Red Liner	0.080 inches 2.03 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS490	Dark Grey / Red Liner	0.090 inches 2.29 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4100	Dark Grey / Red Liner	0.100 inches 2.54 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4110	Dark Grey / Red Liner	0.110 inches 2.79 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4120	Dark Grey / Red Liner	0.120 inches 3.05 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4130	Dark Grey / Red Liner	0.130 inches 3.30 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4140	Dark Grey / Red Liner	0.140 inches 3.56 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4150	Dark Grey / Red Liner	0.150 inches 3.81 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4160	Dark Grey / Red Liner	0.160 inches 4.06 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4170	Dark Grey / Red Liner	0.170 inches 4.32 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4180	Dark Grey / Red Liner	0.180 inches 4.57 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4190	Dark Grey / Red Liner	0.190 inches 4.83 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %
Tflex XS4200	Dark Grey / Red Liner	0.200 inches 5.08 mm	3 secs: 30 to 35 30 secs: 22 to 27	0.32 %	0.08 %

Results 1 - 19 of 19