


阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。


Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .


TOP VIEW



FRONT VIEW




RECOMMENDED PCB PAD LAYOUT



ELECTRICAL CHARACTERISTICS

OCL (2-5 with 3 & 4 shorted), 0.25Vrms, 20KHz, 0A_{dc} = 878 - 1631uH
 DCR (2-3) @ 20°C = 0.210Ω Max.
 DCR (4-5) @ 20°C = 0.210Ω Max.
 DCR (7-9) @ 20°C = 2.10Ω Max.
 DCR (10-12) @ 20°C = 2.10Ω Max.
 HiPot 3,4 to 9,10 = 300Vdc for 1 second.

SCHEMATIC



Notes:

1. All dimensions are in millimeters
2. Tolerances are 0.25 mm except stated otherwise.
3. All soldering surfaces must be coplanar within 0.004 inch.
4. Core to be wrapped with 2 layers of 3M20 x.250" tape.
5. wwlllyy= Date Code R= Revision Level
6. PCB tolerances are +/- .1mm unless stated otherwise.

Cooper Electronic Technologies

3601 Quantum Boulevard, Boynton, Beach, FL. 33426


Transformer, Push-Pull,
5V input; 12Vdc @ 0.250A_{dc},

20-50KHz, 1254 uH
ER 14.5/6, Ver, SMT, 12 pad, gull wing.

SIZE Drawing Number: **CTX02-13665**

A Revision Level C Sheet 3 of 5

CTX02-13665



Dimensions in millimeters

Packaging Information:
 Parts packaged on a
 13" Dia. EIA-481 compliant reel.
 300 parts per reel.