

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Expand the Capacity of Your Micro PLC

A wide variety of expansion units that can be used with CP1E, CP1L, and CP1H series PLC.



Ordering Information

Description	Output type	Input points	Output points	Size in mm (HxWxD)	Model
Expansion I/O units	--	8	--	90x66x50	CP1W-8ED
	Relay	--	8	90x66x50	CP1W-8ER
	Transistor (sinking)	--	8	90x66x50	CP1W-8ET
	Transistor (sourcing)	--	8	90x66x50	CP1W-8ET1
	Relay	--	16	90x86x50	CP1W-16ER
	Relay	12	8	90x96x50	CP1W-20EDR1
	Transistor (sinking)	12	8	90x96x50	CP1W-20EDT
	Transistor (sourcing)	12	8	90x96x50	CP1W-20EDT1
	Relay	24	16	90x150x50	CP1W-40EDR
	Transistor (sinking)	24	16	90x150x50	CP1W-40EDT
	Transistor (sourcing)	24	16	90x150x50	CP1W-40EDT1
Analog I/O units	Analog (resolution 1/256)	2	1	90x66x50	CPM1A-MAD01
	Analog (resolution 1/6000)	2	1	90x86x50	CP1W-MAD11
	Analog (resolution 1/6000)	4	--	90x86x50	CP1W-AD041
	Analog (resolution 1/6000)	--	4	90x86x50	CP1W-DA041
Temperature sensor input units	Thermocouple input	2	--	90x86x50	CP1W-TS001
	Thermocouple input	4	--	90x86x50	CP1W-TS002
	Platinum resistance input	2	--	90x86x50	CP1W-TS101
	Platinum resistance input	4	--	90x86x50	CP1W-TS102

Options for CPU Units

Name	Specifications	Model
RS-232C Option Board	Can be mounted in either CPU Unit Option Board slot 1 or 2. Note: Cannot be used for the CP1L-L10.	CP1W-CIF01
RS-422A/485 Option Board	Can be mounted in either CPU Unit Option Board slot 1 or 2. Note: Cannot be used for the CP1L-L10. Maximum transmission distance: 50m	CP1W-CIF11
RS-422A/485 Isolated-type Option Board	One RS-422A/485 port (Isolated) Note: Cannot be used for the CP1L-L10. Maximum transmission distance: 500m	CP1W-CIF12
LCD Option Board	Can be mounted only in the CPU Unit Option Board slot 1. Note: Cannot be used for the CP1L-L10.	CP1W-DAM01
Memory Cassette	Can be used for backing up programs or auto-booting	CP1W-ME05M
Economical Ethernet Option Board	Two can be mounted in either of CPU Unit Option Board slot 1 and 2. Note: Cannot be used for the CP1L-L10.	CP1W-ETN61
Advanced Ethernet Option Board	One can be mounted in either CPU Unit Option Board slot 1 or 2. Note: Cannot be used for the CP1E or the CP1L-L10.	CP1W-CIF41
Ethernet/IP Slave Option Board	One can be mounted in either CPU Unit Option Board slot 1 or 2. Note: Cannot be used for the CP1E or the CP1L-L10.	CP1W-EIP61
Modbus/TCP Slave Option Board	One can be mounted in either CPU Unit Option Board slot 1 or 2. Note: Cannot be used for the CP1E or the CP1L-L10.	CP1W-MODTCP61
2 Point Thermocouple Option Board	J/K thermocouple, can be mounted in either CPU Unit Option Board slot 1 or 2. Note: Cannot be used for the CP1E.	CP1W-GCTS2
2 Analog Input Option Board	0-10 V, 0-20 mA Note: Only for the CP1L-E	CP1W-ADB21
2 Analog Output Option Board	0-10 V Note: Only for the CP1L-E	CP1W-DAB21V
2 In/2 Out Analog Option Board	Input: 0-10 V, 0-20 mA, Output: 0-10 V Note: Only for the CP1L-E	CP1W-MAB221