

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

## Embedded OEM

### DRAM

DDR3

**DDR2**

DDR

SDR

Speciality

Flash

SSD

ADD2

Modems

[Home](#) > [Embedded OEM](#) > [DRAM](#) > [DDR2](#)

# DRAM DDR2

## SODIMM

RDIMM

UDIMM

SODIMM

mini DIMM


[more images](#)

DDR2 has been the standard memory solutions for applications in virtually all market segments from Servers, PCs and Notebooks to Printers, Networking and Storage systems and many more for several years providing superior cost and performance criteria. DDR2 has started to relinquish its role as the memory industry's mainstream technology to DDR3 and is forecasted to become a legacy product by early 2011

Available in power supply voltages of 1.8V (and 1.55V for FBDIMMs) and with transfer data rates from 400Mb/s to 800Mb/s and beyond, DDR2 has been designed in a wide range of applications providing designers with numerous module options to choose from. Wintec offers a wide range of DDR2 Module solutions. Please click on the link to find out more about our solutions.

### DDR2 - 200-Pin SODIMM - Registered ECC

Standard Profile (1.181") with Nominal Voltage (1.8V)

Density	Part Number	Rank	DIMM Config	Component Config	Voltage
1GB	WD2AE01GX809-xxxx-yyz	1 rank	128x72	128Mx8	1.8V
2GB	WD2AE02GX809-xxxx-yyz	1 rank	256x72	256Mx8	1.8V
4GB	WD2AE04GD809-xxxx-yyz	2 rank	512x72	512Mx8	1.8V

### DDR2 - 200-Pin SODIMM - Unbuffered ECC

Standard Profile (1.181") with Nominal Voltage (1.8V)

Density	Part Number	Rank	DIMM Config	Component Config	Voltage
1GB	WD2SE01GX809-xxxx-yy	1 rank	128x72	128Mx8	1.8V

<b>2GB</b>	WD2SE02GX818-xxxx-yy	2 rank	256x72	128Mx8	1.8V
	WD2SE02GX809-xxxx-yy	1 rank	256x72	256Mx8	1.8V
<b>4GB</b>	WD2SE04GX818-xxxx-yy	2 Rank	512x72	256Mx8	1.8V

## DDR2 - 200-Pin SODIMM - Unbuffered Non-ECC

Standard Profile (1.181") with Nominal Voltage (1.8V)

Density	Part Number	Rank	DIMM Config	Component Config	Voltage
<b>1GB</b>	WD2SN01GX808-xxxx-yy	1 rank	128x64	128Mx8	1.8V
<b>2GB</b>	WD2SN02GX816-xxxx-yy	2 rank	256x64	128Mx8	1.8V
	WD2SN02GX808-xxxx-yy	1 rank	256x64	256Mx8	1.8V
<b>4GB</b>	WD2SN04GX816-xxxx-yy	2 rank	512x64	256Mx8	1.8V
	WD2SN04GX808-xxxx-yy	1 rank	512x64	512Mx8	1.8V

(xxxxx) Modules Speed (MHz) and CAS Latency

= 800I: 800MHz CL6  
 800G : 800MHz CL5  
 667G : 667MHz CL5  
 533E : 533MHz CL4

DRAM Manufacturer and Die Revision

(yy) = P: Samsung                   A: A-Die  
 H: Micron                        B: B-Die  
 C: Hynix                         C: C-Die

Buffer / Register set (Only applies to Registered/Buffered modules)

(z) = I: Inphi  
 D: IDT  
 L: Intel