

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



ATP aMLC (*advancedMLC*) SDHC/microSDHC

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications



ATP aMLC SDHC/microSDHC cards are designed for most up-to-date industrial applications, such as surveillance, medical imaging, transportation, drive recorder and automation where customers require higher reliability, endurance and performance but also seek for cost-effective solution to meet their budget.

ATP aMLC SD/microSD cards are considered as escalation of MLC memory cards. With advanced firmware algorithm, ATP aMLC technology manipulates MLC flash 2 bits each cell into 1 bit to improve aMLC product spec in all respects. ATP aMLC memory cards with overall upgrades, 13X endurance, 1.5X write performance, 5X data retention improvement compared with traditional MLC cards. aMLC is suitable for intensive write applications due to increasing endurance (40K P/E cycles) and enhanced write speed. Nonetheless, it's also a reliable solution for read applications owing to the faster read performance and Read Disturb Protector – AutoRefresh technology to assure the data integrity at the same time.

Moreover, with SIP (System-In-Package) manufacturing process, the operating/storage temperature of ATP aMLC SD/microSD cards is -25 to 85 degrees Celsius. ATP aMLC memory cards passed a series of power cycling test and thorough evaluation process. Each aMLC card will conduct 100% production level burn-in test before delivering to customers.

Key Features

- aMLC (*advancedMLC* technology /1-bit per Cell) NAND Flash
- Advanced Wear Leveling algorithm
- Bad Block Management
- Read Disturb Protector - AutoRefresh to ensure data integrity during read operation
- Enhanced F/W algorithm to minimize the risk of a sudden power-off
- Water proof, Dust proof and ESD resistant
- Highly reliable and pass environmental test (Bend/Torque/Salt Spray/Solar radiation)
- Life Monitor (Note : The compatibility and support of Life Monitor may vary on different platform/operation system)

Applications

- Industrial PCs
- Medical devices
- Automotive IVI systems
- Drive recorders
- Surveillance systems
- Navigations
- Test and Measurement
- Mobile/Handheld computers
- Automation



Specifications

Product Name	SDHC	microSDHC
Flash Type	aMLC	
Density	4GB to 8GB	4GB to 16GB
Performance	Sequential Read up to 74.5MB/s	Sequential Read up to 74.5MB/s
	Sequential Write up to 27.3MB/s	Sequential Write up to 36.2MB/s
Interface	SD3.0 UHS-I Mode	
Operation Temperature	-25°C to +85°C	-25°C to +85°C
Reliability	Advanced Static/Dynamic Wear-Leveling	
	TBW**(max.): 64TB	TBW**(max.):128TB
	MTBF@25C:>3,000,000 hours	
	Number of Insertions: 10,000 minimum	
Dimensions: LxWxH (mm)	32.0 x 24.0 x 2.1	15.0 x 11.0 x 1.0

** All TBW data listed are under highest random write value in each product line. The TBW data are subject to change by density, configuration and customers' applications.

Ordering Information

Density	SDHC	microSDHC
4GB	AF4GSD3A-OEM	AF4GUD3A-OEM
8GB	AF8GSD3A-OEM	AF8GUD3A-OEM
16GB	-	AF16GUD3A-OEM

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368
FAX: +886-2-2659-4982
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
FAX: +1-408-732-5055
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
FAX: +49-89-374-9999-29
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6206-8097
FAX: +81-3-6206-8098
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
FAX: +86-21-9687-0000-026
sales@cn.atpinc.com

