

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .






FX Series

SD Memory Card, Industrial SLC Model

■ Product Outline

FX series are SD/SDHC memory cards adopting built-in industrial type SLC NAND flash memory and is suitable for industrial applications where frequent writes are required. They are adequate for the applications, where large data load are written, such as security camera, factory automation, broadcast equipment and drive recorders. They are formatted complying with SD card specification.

■ Product Specification (specifications and appearances may be changed without notice.)


| | | 512MB | 2GB | 4GB | 8GB | 16GB |
|--------------------------------|---------------------------------------|---|---|--|---|---|
| Appearance | |  |  |  |  |  |
| Part Number | | RP-SDFC51DA1 | RP-SDF02GDA1 | RP-SDF04GDA1 | RP-SDF08GDA1 | RP-SDF16GDA1 |
| Capacity | Available user data area capacity *1) | 495,190,016 byte | 2,014,445,568 byte | 3,955,195,904 byte | 8,048,836,608 byte | 16,194,174,976 byte |
| Compliant Specification | SD Physical Specification | Ver. 3.01 | | | | |
| | SD speed class | CLASS E | | CLASS 10 | | |
| | UHS speed grade | --- | | 1 | | |
| | Speed mode | Default Speed mode, High Speed mode | | Default Speed mode, High Speed mode, UHS-I (SDR12, SDR25, DDR50, SDR50, SDR104) | | |
| Backside mark | Control Code | R0B8 | R2B9 | | | |
| Read/Write Performance (up to) | Read | 22MB/s (High Speed) | | 90MB/s (SDR104) | 95MB/s (SDR104) | |
| | Write | 20MB/s (High Speed) | | 40MB/s (SDR104) | 80MB/s (SDR104) | |
| Absolute Maximum Ratings | Supply Voltage | Min : -0.3 V ; Max : +4.6 V | | | | |
| | Input Voltage | Min : -0.3 V ; Max : VDD +0.3 V | | | | |
| | Output Voltage | Min : -0.3 V ; Max : VDD +0.3 V | | | | |
| | Output Current | Min : -24 mA ; Max : +24 mA | | | | |
| Environmental Specification | Operating Temperature | -40 degree C to +85 degree C | | | | |
| | Storage Temperature | -40 degree C to +85 degree C | | | | |
| | Humidity | 5 % RH to 95 % RH | | | | |
| | Vibration | 15 Gp-p | | | | |
| | Shock | 1,000 G | | | | |
| | Mating Cycles | 10,000 cycles | | | | |

*1) Free user area capacity after formatted.

Absolute Maximum Ratings are the values of limitation, which do not damage the card. So those values do not define the operational range.

Products comply with EU RoHS directives.

■ Laser Mark on the Back-side (example; 2GB)



“0000” Control Code (Defined as product parts combination)
“00YM00000000” Serial Number
Y Last digit of Manufacture year
M Manufacture month (January->A, February->B,)
“2GB” Card Capacity
“F” Series name
“MADE IN JAPAN” Country of origin

■ System Reliability

- Powerful error detect and corrective function
- Static wear leveling
- Data recovery at power failure in writing
- Automatic refresh function to prevent uncorrectable error
- Bad block management

■ Notice and Caution

If you think about the usage for which special quality or reliability of the products is needed and failure or malfunction of the products may directly threaten life or injury for the special usage (aeronautic or cosmic usage, military usage, combustion machine, life support applications or safety applications), please counsel with our contacts in advance.

Write frequency and storage temperature will affect data retention time. Please make a backup for important data.

■ Warranty

If the product cannot be used because of failure which is determined as defect in design or production of the product, it is replaced by same product or equivalent one within 12 months from the delivery date of product.