

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .





PE Series

microSD/SDHC Memory Card, Consumer Plus “SLC Lite” Model

■ **Product Outline**

PE series are microSD/SDHC memory cards adopting built-in consumer type MLC NAND flash memory using an SLC-like access mode. This enables higher endurance/data retention and power fail robustness than Panasonic Consumer Plus MLC model. They are formatted complying with SD card specification.

■ **Product Specification** (specifications and appearances may be changed without notice.)

		2GB	4GB	8GB	16GB
Appearance					
Part Number		RP-SMPE02DA1	RP-SMPE04DA1	RP-SMPE08DA1	RP-SMPE16DA1
Capacity	Available user data area capacity *1)	1,981,480,920 byte	3,971,973,120 byte	7,960,756,224 byte	16,001,236,992 byte
Compliant Specification	SD Physical Specification	Ver. 3.01			
	SD speed class	CLASS 6	CLASS 10		
	UHS speed grade	---	U1		
	Speed mode	Default Speed mode, High Speed mode	Default Speed mode, High Speed mode SDR50, DDR50, SDR25, SDR12		
Backside mark	Control Code	---			
Read/Write Performance (up to)	Read	22MB/s (HS mode)	45MB/s (SDR50, DDR50 mode)	45MB/s (SDR50, DDR50 mode)	45MB/s (SDR50, DDR50 mode)
	Write	20MB/s (HS mode)	35MB/s (SDR50, DDR50 mode)	40MB/s (SDR50, DDR50 mode)	40MB/s (SDR50, DDR50 mode)
Absolute Maximum Ratings	Supply Voltage	Min : -0.3 V ; Max : +4.6 V			
	Input Voltage	Min : -0.3 V ; Max : VDD +0.3 V			
	Output Voltage	Min : -0.3 V ; Max : VDD +0.3 V			
	Output Current	Min : -24 mA ; Max : +24 mA			
Environmental Specification	Operating Temperature	-25 degree C to +85 degree C			
	Storage Temperature	-40 degree C to +85 degree C			
	Humidity	5 % RH to 95 % RH			
	Vibration	15 Gp-p			
	Shock	1,000 G			
	Mating Cycles	10,000 cycles			

*1) Free user area capacity after formatted.

Absolute Maximum Ratings are the values of limitation, which do not damage the card. So those values do not define the operational range.


Products comply with EU RoHS directives.

■ Marking Specification (example; 4GB)



“4GB”
“MADE IN TAIWAN”

Card Capacity
Country of origin



“000000000”
“0000000000000000”

Internal control code
Internal control code

“00YM0000000”
Y
M

Serial Number
Last digit of Manufacture year
Manufacture month
(January->A, February->B, ...)

■ System Reliability

- a. Error detect and corrective function
- b. Static wear leveling
- c. Bad block management

■ Notice and Caution

If you think about the usage for which special quality or reliability of the products is needed and failure or malfunction of the products may directly threaten life or injury for the special usage (aeronautic or cosmic usage, military usage, combustion machine, life support applications or safety applications), please counsel with our contacts in advance.

Write frequency and storage temperature will affect data retention time. Please make a backup for important data.

■ Warranty

If the product cannot be used because of failure which is determined as defect in design or in production of the product, it is replaced by same product or equivalent one within 12 months from the delivery date of product.