

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



ATP Industrial Grade USB Drives

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications



NANODURA / USB Module

ATP Industrial Grade USB Drives are designed for mission critical embedded applications with space constraints, high performance and high data retention requirements. The drives have the extraordinary endurance of 60,000 program/erase cycles, while most MLC-based USB drives on the market have less than 3,000 program/erase cycles. The Industrial Grade USB Drive is ideal for industrial application such as medical, IPC and automation applications.

Key Features

- Enhanced endurance with Advanced Wear Leveling algorithm
- 10 years data retention for SLC-based ATP Industrial Grade USB Drive vs. 6 months for MLC-based USB drives
- System in Package (SIP) Technology: extreme operating temperature: -40°C to 85°C, water/moisture resistance, vibration, shock and electrostatic discharge resistant
- Support S.M.A.R.T ATA feature set
- NSA Compliant SecureErase

Applications

- Medical
- Industrial PC
- Automation applications



Specifications

Product Name	USB Drive-NANODURA	USB Module
Flash Type	SLC	
Capacities	512MB to 8GB	
Performance	Sequential Read up to 21MB/s	
	Sequential Write up to 16MB/s	
Interface	Compatible with USB 2.0(480Mbps)	
Operating Temperature	-40°C to +85°C	
Reliability	Advanced Wear Leveling	
	TBW** (max.) : 96 TB	
	MTBF @ 25°C: >5,000,000 hours	
	Number of Insertions: 10,000 minimum	
Dimensions: LxWxH (mm)	34.0 x 12.2 x 4.5	26.6 x 12.0 x 4.5

** All TBW data listed are under highest random write value in each product line. The TBW data are subject to change by density, configuration and customers' applications.

Ordering Information

Density	USB Drive-NANODURA	USB Module
512MB	AF512UFNDNC(I)-OEM	AF512UFP3NC(I)-OEM
1GB	AF1GUFNDNC(I)-OEM	AF1GUFP3NC(I)-OEM
2GB	AF2GUFNDNC(I)-OEM	AF2GUFP3NC(I)-OEM
4GB	AF4GUFNDNC(I)-OEM	AF4GUFP3NC(I)-OEM
8GB	AF8GUFNDNC(I)-OEM	AF8GUFP3NC(I)-OEM

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368
FAX: +886-2-2659-4982
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
FAX: +1-408-732-5055
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
FAX: +49-89-374-9999-29
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6206-8097
FAX: +81-3-6206-8098
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
FAX: +86-21-5080-2219
sales@cn.atpinc.com

