

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

**LED DISPLAY  
LTD-4830CTB-P**

**LED DISPLAY**

LTD-4830CTB-P

| <u>Rev</u>  | <u>Description</u>                      | <u>By</u> | <u>Date</u> |
|---|---|-----------|-------------|
| 01  | Preliminary Spec.                       | Reo Lin   | 04/20/2011  |
| 02  | Add minimum packing quantity in page 12 | Reo Lin   | 05/08/2014  |
|   |   |           |             |
|   |   |           |             |
|   |   |           |             |
|   |   |           |             |
|   |   |           |             |
| <b>Above data for PD and Customer tracking only</b> |   |           |             |
|   |   |           |             |
|   |   |           |             |
|   |   |           |             |

## LED DISPLAY LTD-4830CTB-P

### 1. Description

The LTD-4830CTB-P is a 0.39 inch (10.0mm) digit height dual digit SMD display. This device uses InGaN blue LED chips (InGaN epi on Sapphire substrate). The display has gray face and white segments.

#### 1.1 Features


- 0.39 inch (10.0 mm) DIGIT HEIGHT
- CONTINUOUS UNIFORM SEGMENTS
- LOW POWER REQUIREMENT
- EXCELLENT CHARACTERS APPEARANCE
- HIGH BRIGHTNESS & HIGH CONTRAST
- WIDE VIEWING ANGLE
- SOLID STATE RELIABILITY
- CATEGORIZED FOR LUMINOUS INTENSITY.
- LEAD-FREE PACKAGE (ACCORDING TO ROHS)

#### 1.2 Device

| Part No       | Description      |
|---------------|------------------|
| InGaN Blue    | Common Anode     |
| LTD-4830CTB-P | Rt. Hand Decimal |

**LED DISPLAY  
LTD-4830CTB-P**

**2. Package Dimensions**




**Notes :**

1. All dimensions are in millimeters. Tolerances are  $\pm 0.25$  mm (0.01") unless otherwise noted
2. Foreign material on segment  $\leq 10$ mil
3. Ink contamination (surface)  $\leq 20$ mils
4. Bubble in segment  $\leq 10$ mil
5. Bending  $\leq 1\%$  of reflector length
6. Plastic pin's burr max is 0.05 mm

**LED DISPLAY  
LTD-4830CTB-P**

**3. Internal Circuit Diagram**



**LED DISPLAY  
LTD-4830CTB-P**

**4. Pin Connection**

| No | Connection           |
|----|----------------------|
| 1  | CATHODE DIGIT1 E     |
| 2  | CATHODE DIGIT1 D     |
| 3  | COMMON ANODE DIGIT 1 |
| 4  | CATHODE DIGIT1 C     |
| 5  | CATHODE DIGIT1 DP    |
| 6  | CATHODE DIGIT1 B     |
| 7  | CATHODE DIGIT1 A     |
| 8  | COMMON ANODE DIGIT 1 |
| 9  | CATHODE DIGIT1 F     |
| 10 | CATHODE DIGIT1 G     |
| 11 | CATHODE DIGIT2 E     |
| 12 | CATHODE DIGIT2 D     |
| 13 | COMMON ANODE DIGIT 2 |
| 14 | CATHODE DIGIT2 C     |
| 15 | CATHODE DIGIT2 DP    |
| 16 | CATHODE DIGIT2 B     |
| 17 | CATHODE DIGIT2 A     |
| 18 | COMMON ANODE DIGIT 2 |
| 19 | CATHODE DIGIT2 F     |
| 20 | CATHODE DIGIT2 G     |

## LED DISPLAY LTD-4830CTB-P

### 5. Rating and Characteristics

#### 5.1. Absolute Maximum Rating at Ta=25°C

| Parameter   | Maximum Rating  | Unit        |
|---|-----------------|-------------|
| Power Dissipation Per Segment   | 70              | mW          |
| Peak Forward Current Per Segment<br>( 1/10 Duty Cycle, 0.1ms Pulse Width )      | 100             | mA          |
| Continuous Forward Current Per Segment<br>Derating Linear From 25°C Per Segment | 20<br>0.21      | mA<br>mA/°C |
| Operating Temperature Range   | -35°C to +105°C |             |
| Storage Temperature Range   | -35°C to +105°C |             |
| Iron Soldering Conditions: 1/16 inch Below Seating Plane for 3 Seconds at 260°C |                 |             |

#### 5.2. Electrical / Optical Characteristics at Ta=25°C

| Parameter   | Symbol | MIN. | TYP. | MAX. | Unit | Test Condition |
|---|--------|------|------|------|------|----------------|
| Average Luminous Intensity Per Segment                    | IV     | 2100 | 7000 |      | μcd  | IF=10mA        |
| Peak Emission Wavelength                                  | λp     |      | 468  |      | nm   | IF=20mA        |
| Spectral Line Half-Width                                  | Δλ     |      | 25   |      | nm   | IF=20mA        |
| Dominant Wavelength                                       | λd     |      | 470  |      | nm   | IF=20mA        |
| Forward Voltage Per Chip                                  | VF     |      | 3.3  | 3.8  | V    | IF=20mA        |
| Reverse Current Per Segment <sup>(2)</sup>                | IR     |      |      | 100  | μA   | VR=5V          |
| Luminous Intensity Matching Ratio<br>(Similar Light Area) | IV-m   |      |      | 2:1  |      | IF=10mA        |

#### Notes :

1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE (Commission International De L'Eclairage) eye-response curve
2. Reverse voltage is only for IR test. It cannot continue to operate at this situation
3. Cross talk specification  $\leq 2.5\%$

# LED DISPLAY LTD-4830CTB-P

### ESD (Electrostatic Discharge)

Static Electricity or power surge will damage the LED. Suggestions to prevent ESD damage:

- Use of a conductive wrist band or anti-electrostatic glove when handling these LEDs.
- All devices, equipment, and machinery must be properly grounded.
- Work tables, storage racks, etc. should be properly grounded.
- Use ion blower to neutralize the static charge which might have built up on surface of the LED's plastic for N/D as a result of friction between LEDs during storage and handling.



## LED DISPLAY LTD-4830CTB-P

### 5.3. Typical Electrical / Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)




Fig1. RELATIVE INTENSITY VS. WAVELENGTH




Fig3. FORWARD CURRENT VS. FORWARD VOLTAGE




Fig4. RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




Fig5. MAX. ALLOWABLE DC CURRENT VS. AMBIENT TEMPERATURE.





Fig6. MAX. PEAK CURRENT VS. DUTY CYCLE %  
(REFRESH RATE 1KHz)

NOTE: TB=InGaN/sapphire Blue

## LED DISPLAY LTD-4830CTB-P

### 6. SMT SOLDERING INSTRUCTION

(Number of reflow process shall be less than 2 times, and cooling process to normal temperature is required between the first and the second soldering process)



#### Notes :


1. Recommended soldering condition

| Reflow Soldering (Two times only) |              | Soldering Iron (One time only) |            |
|-----------------------------------|--------------|--------------------------------|------------|
| Pre-heat:                         | 120~150°C.   | Temperature                    | 300°C Max. |
| Pre-heat time:                    | 120sec. Max. | Soldering time                 | 3sec. Max. |
| Peak temperature:                 | 260°C Max.   |                                |            |
| Soldering time:                   | 5sec. Max.   |                                |            |

2. Number of reflow process shall be less than 2 times, and cooling process to normal temperature is required between the first and the second soldering process.

**LED DISPLAY  
LTD-4830CTB-P**


**7. Recommended Soldering Pattern**



**LED DISPLAY  
LTD-4830CTB-P**


**8. Packing Specification**

**8.1. Packing Reel Dimensions**




## LED DISPLAY LTD-4830CTB-P

### 8.2. Packing Carrier Dimensions



1. 10 sprocket hole pitch cumulative tolerance  $\pm 0.20$ .
2. Carrier camber is within 1 mm in 250 mm.
3. Material : Black Conductive Polystyrene Alloy.
4. All dimensions meet EIA-481-C requirements.
5. Thickness :  $0.30 \pm 0.05 \text{ mm}$ .
6. Packing length per 22" reel : 35.5 Meters.
7. Component load per 13" reel: 550 PCS
8. Minimum packing quantity is 150 PCS for remainders


### 8.3. Trailer part / Leader part



**LED DISPLAY  
LTD-4830CTB-P**

**9. Moisture Proof Packing**

All N/D SMD displays are shipped in moisture proof package. The displays should be stored at 30°C or less and 60% RH or less. Once the package opened, moisture absorption begins.



If the parts are not stored in dry conditions, they must be baked before reflow to prevent damage to the parts. Baking should only be done once

| Package | Temperature | Time      |
|---------|-------------|-----------|
| In Reel | 60°C        | ≥ 48hours |
| In Bulk | 100°C       | ≥ 4hours  |
|         | 125°C       | ≥ 2hours  |