

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .


Graphic VFD Module GU140x16G-7002 [CLICK HERE FOR COMMANDS LIST](#)

Ref. MC-017 Dec.02

- Character Graphic, Transformerless display
- Size compatible with LCD Module (U-Version)
- Single 5V power supply
- High Brightness Blue Green display
- Operating temp -40°C to +85°C
- Proportional and scalable fonts
- Screen saver & window definition function
- 8 level brightness control function
- 8 bit Parallel, CMOS serial Interface

The module includes the Vacuum Fluorescent Display glass, driver and micro-controller lcs with refresh RAM, character generator and interface logic.
 This module have 8 bit parallel & CMOS sync or asyn serial interface.
 The module can simultaneously display graphic pattern and / or characters on screen.

Sample software available



ELECTRICAL SPECIFICATION

Parameter	Symbol	Value
Power Supply Voltage	VCC	5.0VDC
Power Supply Current	ICC	260mADC typ.
Logic High Input	VIH	0.8VDC min. Vcc max.
Logic Low Input	VIL	0VDC min. 0.2VDC max.
Logic High Output	VOH	3.5VDC min. 3.8VDC min.
Logic Low Output	VOL	0VDC min. 0.6 DC max.

OPTICAL and ENVIRONMENTAL SPECIFICATIONS

Parameter	Value
PCB Size (X x Y mm)	80.00 x 36.00
Display Area (X x Y mm)	52.5 x 11.45
Dot size / Pitch (X x Y mm)	0.33 x 0.58 / 0.47 x 0.73
Luminance	700 cd/m ² Typ.
Color of Illumination	Blue Green (Filter for more colors)
Operating Temperature	-40°C to +85°C
Operating Humidity	20 to 80 % RH (non condensing)

SOFTWARE COMMANDS - Popular codes, more includec

Command	Code
Write Character to Display	20H~FFH
Cursor Set	1FH 24H xL xH yL yH
Initialize Display	1BH 40H
Specify International Font	1BH 52H n
Vertical / Horizontal Scroll Mode	1FH 02H / 1FH 03H
Screen Saver	1FH 28H 61H 40H p
Display Blink	1FH 28H 61H 11H p t1 t2 c
Bit Image Display Group	1FH 28H 66H 11H xL xH
Font Magnified Display	1FH 28H 67H 40H x y
Brightness Level Setting	1FH 58H n

COMMON FONT

	2	3	4	5	6	7
x0H	0	1	2	3	4	5
x1H	6	7	8	9	A	B
x2H	C	D	E	F	G	H
x3H	I	J	K	L	M	N
x4H	O	P	Q	R	S	T
x5H	U	V	W	X	Y	Z
x6H	[\	^	_	~	`
x7H	{		~	}	`	`
x8H	~	~	~	~	~	~
x9H	~	~	~	~	~	~
xAH	~	~	~	~	~	~
xBH	~	~	~	~	~	~
xCH	~	~	~	~	~	~
xDH	~	~	~	~	~	~
xEH	~	~	~	~	~	~
xFH	~	~	~	~	~	~

INTERNATIONAL FONTS

	8	9	A	B	C	D	E	F
x0H	0	1	2	3	4	5	6	7
x1H	8	9	A	B	C	D	E	F
x2H	G	H	I	J	K	L	M	N
x3H	O	P	Q	R	S	T	U	V
x4H	W	X	Y	Z	[\	^	_
x5H	~	~	~	~	~	~	~	~
x6H	~	~	~	~	~	~	~	~
x7H	~	~	~	~	~	~	~	~
x8H	~	~	~	~	~	~	~	~
x9H	~	~	~	~	~	~	~	~
xAH	~	~	~	~	~	~	~	~
xBH	~	~	~	~	~	~	~	~
xCH	~	~	~	~	~	~	~	~
xDH	~	~	~	~	~	~	~	~
xEH	~	~	~	~	~	~	~	~
xFH	~	~	~	~	~	~	~	~

n=0
n=19

CMOS Serial Interface - CN2

Pin	Asyn. Sig	Syn. Sig
1	Vcc	Vcc
2	SIN	SIN
3	GND	GND
4	SBUSY	SBUSY
5	NC	SCK
6	/RESET	/RESET

Parallel Interface - CN1

Pin	Sig	Pin	Sig
1	GND	2	Vcc
3	NC	4	RS
5	/W	6	/RD
7	D0	8	D1
9	D2	10	D3
11	D4	12	D5
13	D6	14	D7

Please inquire for full specification.

** Subject to change without notice **