

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

DC to 65 GHz, HV Connector Attenuators

HV-AT Series



Overview

Small, lightweight and low V.S.W.R makes it ideally suited for the widely used high frequency transmission applications.

Frequency bandwidth and high reliability is achieved by the use of resistance substrate on the extremely thin board, to form a suspended line.

HRS unique resistance substrate design and center conductor connection assures consistent and stable performance in changing temperature environments.

Features

- 1. Low V.S.W.R.**
1.4 (Typical DC to 65 GHz)
- 2. Space-saving design**
Overall dimensions: 9 mm dia. x 24.64 mm long.
- 3. Lightweight**
Total weight: 5.86 g.
- 4. Mating compatibility**
Will mate with corresponding V Connector™ or 1.85mm connector. (Note)
- 5. RoHS compliant**
All components and materials comply with EU Directive 2002/95/EC.

Applications

- * Optical transmission devices
- * Network analyzers
- * BERTS (Bit Error Ratio Testing Systems)
- * FWA (Fixed Wireless Access)
- * Measurement applications requiring transmission frequencies of up to 65 GHz.

Note: V Connectors is a registered trademark of Anritsu Corporation.

Specifications

Rating	Frequency range Characteristic impedance Power Weight	DC to 65GHz 50Ω 1W CW (At 65°C) 5.86g	Operating temperature range Operating relative humidity	-10°C to +65°C 90% max.
--------	--	--	--	----------------------------

Part No.	Attenuation (dB)				V.S.W.R. (Max)				RoHS
	DC~18GHz	18~26.5GHz	26.5~40GHz	40~65GHz	DC~18GHz	18~26.5GHz	26.5~40GHz	40~65GHz	
HV-AT(0)-PJ	0 ^{+0.4}	0 ^{+0.5}	0 ^{+0.8}	0 ⁺¹	1.35	1.4	1.55		YES
HV-AT(3)-PJ	3 ^{+0.6} _{-0.4}	3 ^{+0.7} _{-0.4}	3 ^{+0.9} _{-0.4}	3 ^{+1.5} _{-0.4}	1.4		1.55		
HV-AT(6)-PJ	6 ^{+0.7} _{-0.3}	6 ^{+0.8} _{-0.3}	6 ^{+0.9} _{-0.3}	6 ^{+1.5} _{-0.3}	1.4		1.6		
HV-AT(10)-PJ	10 ^{+0.9} _{-0.7}	10 ^{+0.4} _{-0.7}	10 ^{+0.6} _{-0.7}	10 ^{+1.5} _{-0.7}	1.4		1.6		
HV-AT(20)-PJ	20 ^{+0.7} _{-0.3}	20 ^{+0.9} _{-0.3}	20 ^{+1.1} _{-0.3}	20 ^{+1.3} _{-0.3}	1.4		1.6		

Item	Specification	Conditions
1.Vibration	No electrical discontinuity of 1 μ s sec. max. No damage, cracks, or parts dislocation.	Frequency 10 to 55 Hz, single amplitude of 1.5mm, 3 axis, duration of 2 hours.
2.Shock	No electrical discontinuity of 1 μ s sec. max. No damage, cracks, or parts dislocation.	Acceleration of 490m/s ² , sine half-wave waveform, 3 cycles in each of the 3 axis.
3.Temperature cycle	No damage, cracks, or parts dislocation.	Temperature: -55 $^{\circ}$ C \rightarrow 15 $^{\circ}$ C to 25 $^{\circ}$ C \rightarrow 125 $^{\circ}$ C \rightarrow 15 $^{\circ}$ C to 25 $^{\circ}$ C Duration (Minutes): 30 \rightarrow 2 to 3 \rightarrow 30 \rightarrow 2 to 3 100 cycles
4.High temperature exposure	No damage, cracks, or parts dislocation.	48 hours at 125 $^{\circ}$ C
5.Low temperature exposure	No damage, cracks, or parts dislocation.	48 hours at -55 $^{\circ}$ C
6.Corrosion resistance	No corrosion	5% salt water solution, 48 hours at 35 $^{\circ}$ C

Materials and Finishes

Components	Material	Finish
Shell	Stainless steel	Passivated
Coupling		
Insulator	PTFE (Polytetrafluoroethylene)	————
Male contact	Brass	Gold plated
Female contact	Berylium copper	Gold plated
Attenuation element	Metal film	————


Ordering information

HV-AT (※※) - PJ






① ② ③ ④

① Series name	: HV Series
② AT	: Attenuator
③ Attenuation	: 0 ... 0 dB
④ Connector type	: PJ ... Plug · jack

Plug-Jack type Attenuator



Typical data



Usage Precautions

1. The center pin contact is 0.511mm diameter. Exercise care when handling the attenuator as NOT to damage or deform this contact. When mating the attenuator with corresponding connector rotate only the hex part. Do not apply axial loads to the center contact or the attenuator body itself.
2. Keep both mating ends free of contamination. If needed, they can be cleaned with alcohol.