

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



* No Relief Version
Shown Here

ETHERNET CONNECTOR SYSTEM

The patented RJ45-ECS Ethernet connector system, available exclusively from Laird Technologies, is a field replaceable outdoor rated and shielded Ethernet connection system for high speed 10BaseT, 100BaseT and 1000BaseT networks. The system features a shielded RJ45 receptacle mounted in a UV protected housing and a mating cable gland which passes an RJ45 connector and seals the cable to IP67 requirements. The system provides for quick and easy disconnect and reconnect of equipment. Because of its many unique design features and low cost, the RJ45-ECS is a universal solution for many industries where a sealed and waterproof, yet removable, Ethernet connection is required. These include outdoor applications such as wireless equipment or video surveillance equipment, and indoor applications such as equipment used in factory automation or harsh industrial processes.

RJ45 connectors are not designed for high reliability in the presence of moisture, dust, or corrosive elements. For this reason, the IP67 sealing ability of the RJ45-ECS provides a reliable connection, even in very harsh environments, for many years of trouble free service. The shielded nature of the Cat5e cable and connectors provide maximum shielding against external EMI for consistent data communications.

For modern wireless systems, the quick disconnect feature allows for ready replacement of rooftop equipment, to minimize field time spent servicing customer's equipment, and minimizing downtime for the customer. This helps to increase operator profitability and customer satisfaction.

FEATURES

- Patented low cost design
- Field replaceable waterproof connector system for RJ45 shielded or unshielded connectors
- Constructed of UV protective materials for long life in harsh outdoor environments
- Seal meets IP67 criteria
- Shock and vibration resistant
- Positive locking RJ45 connector
- 12 in Cat5E strain relieved cable

MARKETS

- Wireless base stations
- Telecom equipment
- Wireless client radios
- 802.11 a/b/g wireless systems
- Direct burial equipment
- 10BaseT, 100BaseT or 1000BaseT networks
- Industrial process control
- Factory automation
- WiMAX

global solutions: local support.™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com



Specifications

Data	10BaseT, 100BaseT and 1000BaseT Networks CAT5e per TIA/EIA 568B ClassD per ISO/IEC 11801
Mechanical	Mating Cycles >500 Positive RJ45 bayonet coupling Cat5 Cable Strain Relief
Material	UV Resistant Nylon 66
Sealing	IP67
Salt Spray	>1000 h
Flammability	UL94VO
Thermal Shock	10 cycles -40 to +100°C
Temperature Range	-40°C to +85°C
Installation Hole Dia	0.787 in (20 mm)
Overall Size (L x Dia)	3.75 in x 1.18 in (95 x 30 mm)
Weight	2 oz (57 gm)

SYSTEM ORDERING INFORMATION

RJ45-ECS	12 in RJ45 Waterproof Outdoor Ethernet Connector System
RJ45-ECS-NR	12 in RJ45 Waterproof Outdoor Ethernet Connector System with no relief
RJ45-ECS-4	4 in RJ45 Waterproof Outdoor Ethernet Connector System
RJ45-ECS-4-NR	4 in RJ45 Waterproof Outdoor Ethernet Connector System with no relief
RJ45-ECS-6	6 in RJ45 Waterproof Outdoor Ethernet Connector System
RJ45-ECS-6-NR	6 in RJ45 Waterproof Outdoor Ethernet Connector System with no relief

NOTES

- All shipments F.O.B. Schaumburg, IL 60173

ANT-DS-RJ45-ECS 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.