

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

TRIUMF™ MMPA Module with Quad-Band GSM/EDGE and Penta-Band W/CDMA/HSPA+/LTE

Part # TQP9058

End of Life announced October 12, 2015 ~ December 2, 2015.

Last Time Buy May 20, 2016.

Last Time Buy Contact your local sales representative for assistance.

Please use TQP9058H as a replacement.

Key Features

- Quad-Band Linear GSM/EDGE
- UMTS B1,2,3/4 and B5,8
- Input power controlled – GMSK and 8PSK
- GSM has 2 modes – HPM, LPM
- W/CDMA has 2 modes – HPM, LPM
- HBT / CuFlip™ PA Technology
- Integrated coupler and Band distribution switches
- Built-in voltage regulator
- 50 ohm input and output impedance
- Lead-free 260 C / RoHS / Halogen-free
- 42 Pin 5x7x1.0 mm package

Description

The TQP9058 is a fully matched multimode multiband Power Amplifier Module that supports Quad-band Linear GSM/EDGE, W/CDMA & LTE Bands 1, 2, 3/4, 5 & 8. The GSM PA output power is controlled by the input power coming from the transceiver in both GMSK and 8PSK modes. The 2-Gain state WCDMA PA operates in LPM and HPM to maximize talk time over the entire range of operating conditions. It also includes a coupler and built-in regulator, ideal for today's extremely small data enabled phones.

The TQM7M9050 is designed on TriQuint's GaAs HBT technology with CuFlip™ assembly offering state of the art reliability, temperature stability and ruggedness. RF performance meets the stringent linearity requirements for multimode operation.

Specifications

Size (mm)	7.0 x 5.0 x 1.0
Bands	GSM850 / 900, DCS / PCS & WCDMA & LTE B1, B2, B3/4, 5 and 8
Features	High / Low Power Modes
RoHS	Yes
Lead Free	Yes
Halogen Free	Yes

Typical Applications

Datacards	M2M
GSM / CDMA / WCDMA / LTE	Mobile Devices
Handsets	Tablets

Additional Information

Status	Last Time Buy
---------------	---------------