

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

APPROVAL SHEET

PCB ANTENNA

2.4 GHz Band Working Frequency

Halogens Free Product

P/N: RFPCA331630IMAB301

Customer : _____
Customer 's Part No. : _____
Approval No. : _____
Issue Date : _____

*Contents in this sheet are subject to change without prior notice.

Version	Date	Description	Author
V01	2015 Oct.	New Release	HWCHAN

ELECTRICAL CHARACTERISTICS

Item	Specification
Frequency Range	2.4 ~ 2.5 GHz
Impedance	50 Ohm Nominal
Return Loss	-10 dB (Max)
Peak Gain	3.96 dBi
VSWR	2.0 (Max)
Radiation	Omni-directional
Polarization	Linear Vertical
Admitted Power	1W

*note-1: Electrical characteristics will depend on customer's final application.


MATERIAL TABLE

Items	Description
Cable	∅ 1.13(Gray)
FPC Antenna	FR4(綠漆板) T=0.6mm
Connector	IPEX

ORDERING RULE

RF	PCA	3316	30	I	M	A	B	3	01
Type Code	Product Code	PCB Dimension (Unit: mm)	Cable Length (unit: cm)	Connector Brand	Type of Connector	Application	Project status	Wire Diameter	Project
Walsin RF Device	PCA: PCB Antenna	Per 2 digits of length, width e.g.:3316 Length 33.5mm, Width 16.6mm	2 digits for cable length e.g.:30 Cable Length:30cm	A: N C:MCX D:IPEX III E: IPEX IV F: IPEX A13 H: Hirose I: IPEX M: MMCX S: SMA T: TNC U:MURATA N: None	A: Reverse Female B: Reverse Male F: Female M: Male N: None	0: 0GHz 3: 3GHz 5: 5GHz 6: 6GHz A: 2.4GHz ISM band B: GSM 900/1800 dual band G: GPS band L: 2.4/5.2/5.8 GHz tri-band N: NFC T: LTE band W: WCDMA band	B: MP T: Durin g Test X: Pile Run	0:None 1:∅ 0.81 3:∅ 1.13 6:RG316 7:∅ 1.37 8:RG178	01-99 series number

Appendix A: Dimensions



Test Report



ELECTRICAL CHARACTERISTICS

Return Loss




■ Antenna Efficiency & Peak Gain

2450 MHz



Maximum Efficiency at 2490 MHz : 67.18%




Maximum Peak Gain at 2450 MHz : 3.96 dBi

RADIATION PATTERN

2400~2500 MHz

Phi=0.00deg


Gain . dB



	ZX plane	
Frequency [MHz]	Max Value [dB]	Average [dB]
2400	0.02	-4.00
2450	-0.39	-4.02
2500	-0.42	-4.02

Phi=90.00deg


Gain . dB



	ZY plane	
Frequency [MHz]	Max Value [dB]	Average [dB]
2400	3.92	0.26
2450	3.96	0.21
2500	3.55	-0.04

Theta=90.00deg

Gain . dB



	XY plane	
Frequency [MHz]	Max Value [dB]	Average [dB]
2400	3.56	-2.85
2450	3.23	-2.92
2500	2.28	-2.97