

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Antenna - RAD-ISM-900-ANT-OMNI-0-N - 5604160


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

2 dBi omnidirectional antenna with base plate and N (female) connection for 900 MHz

Product description

2 dBi omnidirectional antenna with base plate and N (female) connection for 900 MHz

Key commercial data

Packing unit	1
Minimum order quantity	10
GTIN	 4 046356 288743
Weight per piece (including packing)	0.0 GRM
Weight per Piece (excluding packing)	273.9 GRM
Country of origin	UNITED STATES

Technical data

General data

Frequency range	900 MHz
Frequency range	890 MHz ... 960 MHz
Horizontal beamwidth	360 °
Gain	2.15 dBi
Connection method	Type N (female)
Height	88.9 mm
Diameter	3.175 mm
Cable type	RG-58
Fixed cable length	3.00 in.

Classifications

eclass

eClass 4.0	27250312
eClass 4.1	27250312
eClass 5.0	19070102
eClass 5.1	19070102
eClass 6.0	19070102

etim

ETIM 2.0	EC000416
ETIM 3.0	EC001698
ETIM 4.0	EC000416

Antenna - RAD-ISM-900-ANT-OMNI-0-N - 5604160

Classifications

unspsc

UNSPSC 6.01	43171611
UNSPSC 7.0901	43221706
UNSPSC 11	43171611
UNSPSC 12.01	43221706
UNSPSC 13.2	43221706

© Phoenix Contact 2012 - all rights reserved
<http://www.phoenixcontact.com>