

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



Type 1DX

Order Number LBEE5KL1DX

2.4GHz Wi-Fi + Bluetooth 4.1 EDR Module
Network Topology: AP & STA dual mode
Chipset: Broadcom BCM4343W
Processor: No
Modulation: DSSS / CCK / OFDM

Description

The Type 1DX module is an ultra-small module that includes 2.4GHz WLAN and Bluetooth functionality. Based on Broadcom BCM4343W, the module provide high-efficiency RF front end circuits. The module is designed to fit into small spaces and is smaller than a dime. Minimal external circuitry is required to complete a radio design; add an antenna, power source, clocks, processor, and associated interface hardware and the radio hardware design is complete. To ease Wi-Fi certification, the Type 1DX module complies with IEEE 802.11b/g/n and Bluetooth Version 4.1 plus EDR, Power Class 1 (10dBm max) + BLE. Software is available for Linux and Android.

Specs

Product Type	Module
Grade	Consumer
Frequency	2.4GHz
Frequency MHz (min)	2400
Frequency MHz (max)	2483.5
Chipset	Broadcom BCM4343W
Processor	No
Modulation	DSSS / CCK / OFDM
Embedded Stack	No
Antenna	External
Sleep Clock	Yes
System Clock	Internal X'tal
Operating Temperature Range	-30 to +70C
Operating Temperature °C (min)	-30
Operating Temperature °C (max)	70
Mounting Type	SMT
Package	LGA
Dimension	6.95 x 5.15 x 1.1 mm
Supply Voltage (Vdc)	3.6
Supply Voltage min	3.35 for VBAT
Supply Voltage max	4.2 for VBAT
Transmit Power	+17dBm / 11Mbps
Transmit Mode Current	370mA / 11Mbps
Receive Mode Current	60mA
Data Rate WLAN	11, 54, 65 Mbps
Data Rate Bluetooth	3Mbps
WLAN	802.11b/g/n
Bluetooth	v4.1+EDR
Power Class	Class 1 (10 dBm max)
Technology	Wi-Fi + Bluetooth 4.1 EDR
Network	AP & STA dual mode
Host Interface	SDIO
I/O Interface	PCM for BT audio
Host Interface Other	No
Host Interface BT	UART
Interface Voltage (Vdc for VIO)	1.8 or 3.3
FCC/IC Certified	No
ETSI Certified	No
RoHs Compliant	Yes
ECCN	5A992
ISO9001	No
TS16969	No

Block Diagram

