

## 阅读申明


- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

# ZMN-2400 2.4GHz ZIGBEE™ WIRELESS MESH NETWORKING MODULE

Occupying less than one square inch of space, the low cost, low power ZMN-2400 module is ideal for higher data rate applications including industrial sensors, building and home automation and any other applications requiring low power consumption RF communications. The 2.4GHz, license-free band is also widely accepted internationally.



Actual size

**ZigBee/802.15.4.** The ZMN-2400 is fully 802.15.4 and ZigBee compliant, running a ZigBee stack with Cirronet's CSM profile. The ZMN-2400 can operate as a reduced function device (RFD) for end devices to consume the least amount of power, or as a full function device (FFD) to act as a base radio in a star network or a router in a mesh network.

**Industrial Networking.** Although well-suited for home and commercial environments, the ZMN-2400 has a full industrial temperature operating range, -40°C to +85°C. Building on Cirronet's many years of developing products for industrial applications, the ZMN-2400 is uniquely designed with Cirronet's proprietary technology that guarantees industrial-grade performance.

**Rapid & Cost-Effective Integration.** The ZMN-2400 is treated just like other integrated circuits. Even though it is a complete RF module, it is reflow soldered to the host PCB - there is no need for expensive, unreliable connectors, and with its small footprint, there is no size penalty for using a module.

Cirronet has relied on its experience in helping hundreds of OEMs integrate Cirronet modules to create a full set of development and configuration tools.

**FCC Certification/CE Marked.** Cirronet has built the ZMN-2400 module to allow FCC certification and CE Marking as a module. This means FCC & CE type acceptance testing is not required for the device into which the module is integrated, saving you money and getting your product to market faster.

**Experience.** Cirronet's extensive RF experience goes into every ZMN-2400 module. Our RF know-how and practical engineering have made Cirronet the choice of hundreds of OEMs. OEMs know they can rely on Cirronet products and can count on Cirronet's unsurpassed technical support to help them get their products to market.

**Let us be your experts.** Cirronet has delivered high-performance wireless products since 1987. To find out how to put our experience to work for you, call **+1.678.684.2000** or visit our website at **www.cirronet.com**

## FEATURES:

- 2.4 GHz direct sequence spread spectrum technology
- Ad hoc mesh network
- Low power consumption
- Small size, light weight
- FCC certified & CE marked for unlicensed operation

## BENEFITS:

- Worldwide license-free operation
- Fast acquisition time
- Redundant, self healing network
- Supports large number of nodes
- Ideal for battery operation
- Easy to integrate
- Shortens time to market
- Low cost



**CIRRONET.**

An ISO 9001:2000 Certified Company

# ZMN2400 SPECIFICATIONS

## GENERAL SPECIFICATIONS

RF Frequency	2401 - 2483.5 MHz
Spreading Method	Direct sequence
Modulation	O-QPSK
Transmit Power	0 dBm into 50 ohms
Receive Sensitivity	-94 dBm for 10 <sup>-5</sup> BER
RF Channels	16
RF Data Rate	250 Kbps
I/O	1 – SPI port 6 – General purpose I/O lines 3 – 10-bit ADCs 2 – PWMs 1 – UART
Operating Voltage	2.7Vdc – 5.5Vdc
Current Consumption	Sleep – 25 $\mu$ A@3.3V Receive – 35 mA@3.3V Transmit – 30 mA@3.3V
Operating Temperature	-40°C to +85°C

## CONNECTOR PINOUT

Pin 1 - VBATT	Pin 36 - GND
Pin 2 - GND	Pin 35 - RF
Pin 3 - PWMA	Pin 34 - GND
Pin 4 - PWMB	Pin 33 - GND
Pin 5 - GPIO0	Pin 32 - MISO
Pin 6 - GPIO1	Pin 31 - MOSI
Pin 7 - GPIO2	Pin 30 - SCLK
Pin 8 - GPIO3	Pin 29 - EN
Pin 9 - GPIO4	Pin 28 - GND
Pin 10 - GPIO5	Pin 27 - ADC3
Pin 11 - GND	Pin 26 - ADC2
Pin 12 - TDO	Pin 25 - ADC1
Pin 13 - TRST	Pin 24 - RESET
Pin 14 - TCK	Pin 23 - TX_RX
Pin 15 - TMS	Pin 22 - UART_TX
Pin 16 - TDI	Pin 21 - UART_RX
Pin 17 - GND	Pin 20 - GND
Pin 18 - GND	Pin 19 - GND

## PHYSICAL SPECIFICATIONS

