

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Philips' Contactless Mifare® Smart Card ICs

Product Features	Mifare® Ultralight MF0 IC U1X	Mifare® Std 1k MF1 IC S50	Mifare® Std 4k MF1 IC S70	Mifare® DESFire MF3 IC D40	Mifare® DESFire SAM MF3 IC D40 SAM
Memory					
EEPROM size [byte]	64	1024	4096	4096	72k
OTP area [bit]	32	-	-	-	-
Write Endurance [cycles]	10 000	100 000	100 000	100 000	100 000
Data Retention [yrs]	5	10	10	10	10
Organization	16 pages á 4 byte	16 sectors á 64 byte	32 sectors á 64 byte 8 sectors á 256 byte	flexible file system	128 key entries
RF-Interface					
Acc. to ISO 14443A	yes - up to layer 3	yes - up to layer 3	yes - up to layer 3	yes - up to layer 4	ISO 7616,T=1
Frequency [MHz]	13.56	13.56	13.56	13.56	1 ... 10
Baudrate [kbit/s]	106	106	106	106 ... 424	9.6 ... 1000
Anticollision	bit-wise	bit-wise	bit-wise	bit-wise	-
Operating Distance [mm]	up to 100	up to 100	up to 100	up to 100	-
Security					
Unique Serial Number [byte]	7, cascaded	4	4	7, cascaded	7
Random Number Generator	-	yes	yes	yes, according to FIPS140-2	yes
Access Keys	-	2 keys per sector	2 keys per sector	14 keys per application per file	128 key entries per key entry
Access Conditions	per page	per sector	per sector	-	-
Mifare® Classic Security	-	supported	supported	-	-
DES & DES3 Security	-	-	-	MACing / Encipherment	MACing / Encipherment
Anti-tear supported by chip	-	for value blocks	for value blocks	yes	-
Special Features					
Multi-application	-	supports MAD*	supports MAD2**	28 applications, MAD3***	-
Purse Functionality	-	Value block format	Value block format	Value file	-
Secure Transport Transaction	48 byte read 16 byte write	512 byte read 16 byte write	512 byte read 128 byte write	512 byte read 128 byte write	-
Transaction Time [ms]	31.4	164	140	105	-
Packaging					
Sawn Wafer	-	MF1ICS5005W/V9D	MF1ICS7001W/V9D	MF3ICD4001DW/V506	-
Sawn Wafer (Au-Bumped)	MF0ICU1X01W/V1D	MF1ICS5005W/V1D	MF1ICS7001W/V1D	MF4ICD4001DW/V406	-
MOA2 Module	-	MF1MOA2S50/D3F	-	-	-
MOA4 Module	-	MF1MOA4S50/D	MF1MOA4S70/D	MF3MOD4001DV/406	-
FCP2 Module	MF0FCP2U1X/DH	MF1FCP2S50/DH	-	-	-
PDM1.1 Module	-	-	-	-	P5CT072EVO/TOM68220

*MAD: Mifare® Application Directory

**MAD2: MAD Extension for 4 kbyte EEPROM size

***MAD3: MAD2 Extension for DESFire