

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

SCA114T and SCA124T Series

Stand Alone Inclinometer

Current Output

FEATURES

- $\pm 30^\circ$ or $\pm 90^\circ$ for inclination measurement
- 4...20mA current loop output
- 10...36V supply voltage
- High repeatability/stability 0,03°
- >20 000g shock resistant sensing element
- IP67 housing
- Standard M12 sensor connector
- Reverse polarity protected

BENEFITS

- Excellent long term stability
- Outstanding shock durability
- Harsh environment robustness

APPLICATIONS

- Platform tilt measurement
- Equipment and instrument condition monitoring
- Inclination based position measurement
- Rotational orientation measurement (dual axis)

For customised product please contact VTI Technologies

ELECTRICAL CHARACTERISTICS

Parameter	Condition	Min.	Typ	Max.	Units
Supply voltage	Non stabilized	10		36	V
Output	Current output	4		20	mA
Output ¹⁾	Voltage output	1		5	V
Output ²⁾	Voltage output	0		10	V

PERFORMANCE CHARACTERISTICS

Parameter	Condition	SCA114T-D02FA	SCA114T-D04FA	SCA124T-D02FA	SCA124T-D04FA	Units
Measuring range (FS)		± 30	± 90	± 30	± 90	°
Measuring direction	(see "Directions")	X	X	X-Y	X-Y	
Repeatability ³⁾	@ 0° position	<0.03	<0.03	<0.03	<0.03	°
Resolution / Noise	DC ... 10 Hz	0.003	0.003	0.003	0.003	°
Offset ^{4,5)}	0° position	12	12	12	12	mA
Offset accuracy ⁵⁾	Deviation @ 0°	0.08	0.25	0.08	0.25	°
Sensitivity ³⁾		± 8	± 8	± 8	± 8	mA/FS
Cross-axis sensitivity ⁶⁾		4	4	4	4	%
Frequency response	LP (-3 dB point) ⁷⁾	1	1	1	1	Hz
Operating temperature		-40 ... +85	-40 ... +85	-40 ... +85	-40 ... +85	°C
Long term stability	500 h @ 23°C	0.03	0.03	0.03	0.03	°
Housing	Closed connector	IP67	IP67	IP67	IP67	

Note 1. Output current measured over 250Ω load resistor.

Note 2. Output current measured over 500Ω load resistor.

Note 3. Output function trigonometrical (sine curve); $\varphi = \arcsin(I_{out})$

Note 4. Offset specified as Output @ 0°.

Note 5. Mounting accuracy depending. Position should be calibrated. See measuring positions.

Note 6. The cross-axis sensitivity determines how much acceleration or inclination, perpendicular to the measuring axis, couples to the output. The total cross-axis sensitivity is the geometric sum of the sensitivities of the two axes which are perpendicular to the measuring axis.

Note 7. The output has true DC (0Hz) response.

MEASURING DIRECTIONS




Figure 1. Positionst

Notes:

- It is important that the part is parallel to the mounting plane, and that the output equals the zero value when sensor is in zero position.
- Please note the picture above which provides information on how the output of the accelerometer behaves in different circumstances when assembled. Please also note that you can rotate the part around the measuring plane for optimum mounting location.

ELECTRICAL CONNECTION

Pin#	Function
1	X-axis 4...20mA
2	X-axis 4...20mA
3	Y-axis 4...20mA
4	Y-axis 4...20mA
5	Shield (GND)

MECHANICAL SPECIFICATION

Total weight: approx. 200 grams
 Protection class: IP67
 Housing: Anodized aluminium

Mounting

The sensor module is to be mounted with 3 screws, dimension M6.
 Mounting torque 10 ± 2 Nm.

SENSOR DIMENSIONS

Dimensions in mm.

