

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。



Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



ACCU-CURVE™ Thermistors

Ametherm manufactures precision resistance-temperature matched ACCU-CURVE™ thermistors. These devices offer **interchangeability over a broad temperature range** and eliminate the need to individually calibrate or provide circuit compensation for part variability. Accurate temperature measurement to $\pm 0.2^{\circ}\text{C}$ is available over the 0°C to 70°C temperature range. Standard ohmic values at 25°C range from **2,252 to 100,000** ohms.



ACCU-CURVE™ Selection Considerations

- Determine Resistance Value and Temperature Coefficient
- Review Power Dissipation
- Select Temperature Range
- Review Thermal Time Constant

ACCU-CURVE™ Specifications

| Part Number | R @ 25°C | Accuracy in °C | Beta | DC @ 25/85 MW/OC | Time Constant | Coating |
|-------------|----------|----------------|------|------------------|---------------|-------------|
| ACC-001 | 2252 | ± 0.2°C | 3988 | 1 mw/°C | 7 sec | Black Epoxy |
| ACC-011 | 2252 | ± 0.5°C | 3988 | 1 mw/°C | 7 sec | Black Epoxy |
| ACC-021 | 2252 | ± 1.0°C | 3988 | 1 mw/°C | 7 sec | Black Epoxy |
| ACC-004 | 10,000 | ± 0.2°C | 3988 | 1 mw/°C | 7 sec | Black Epoxy |
| ACC-014 | 10,000 | ± 0.5°C | 3988 | 1 mw/°C | 7 sec | Black Epoxy |
| ACC-024 | 10,000 | ± 1.0°C | 3988 | 1 mw/°C | 7 sec | Black Epoxy |
| ACW-005 | 30,000 | ± 0.2°C | 4240 | 1 mw/°C | 7 sec | Black Epoxy |
| ACW-015 | 30,000 | ± 0.5°C | 4240 | 1 mw/°C | 7 sec | Black Epoxy |
| ACW-025 | 30,000 | ± 1.0°C | 4240 | 1 mw/°C | 7 sec | Black Epoxy |
| ACW-007 | 100,000 | ± 0.2°C | 4240 | 1 mw/°C | 7 sec | Black Epoxy |
| ACW-017 | 100,000 | ± 0.5°C | 4240 | 1 mw/°C | 7 sec | Black Epoxy |
| ACW-027 | 100,000 | ± 1.0°C | 4240 | 1 mw/°C | 7 sec | Black Epoxy |

Application

There are numerous ways of measuring temperature electronically. Improvements in thermistor technology, coupled with the introduction of **integrated circuitry**, have made precision temperature measurement systems very cost effective.

Microprocessors, A/D converters, interface electronics and displays are readily available. **Circuit designs with built-in thermistor resistance-temperature algorithms** have gained wide spread acceptance in precision temperature metrology.

Ametherm's ACCU-CURVE™ style thermistors are used in many applications that require a **high degree of accuracy and reliability**. They commonly perform

Accu-Curve Interchangeable Thermistor | Ametherm

temperature sensing, control, and compensation for medical, industrial, and automotive applications.

Interchangeable ACCU-CURVE™ NTC thermistors are usually selected when a high degree of measurement accuracy is required over a wide temperature range. By modifying the Alpha equation, the **resistance and temperature tolerances** can be calculated for various temperature intervals.

Because thermistors are non-linear with respect to their resistance-temperature characteristics, Alpha therefore is non-linear across their resistance-temperature range. As an example, a thermistor material curve with an Alpha of **-4.4%/°C @ 25°C** will have an Alpha of **-3.8%/°C @ 50°C**. For practical applications we recommend that the standardized R/T curves be used.

Ametherm ACCU-CURVE™ thermistors can dissipate **1mW/°C**. As a result, the possibility of error induced by excessive current flow, which would defeat the level of accuracy these devices are capable of representing, may exist in some circuits. To prevent this type of error, Ametherm recommends that circuit design engineers select the highest R value their circuit will tolerate for applications **> 5 Volts** to minimize any self-heating of the thermistor device. Refer to the ACCU-CURVE™ Specifications table for resistance values and temperature tolerances.

Ametherm offers two standard R/T curves, "C" & "W", with temperature coefficients of resistance of **-4.4%/°C and -4.7%/°C**, and Beta (β) values of **3965°K and 4250°K**. To determine the nominal resistance value of a thermistor at a specified temperature, multiply its resistance at **25°C** value by the corresponding **RT/R25** value for the desired temperature and applicable **R-T curve** from the ACCU-CURVE™.

ACCU-CURVE™ Specifications

| Resistance @ 25° C (ohms) | Temperature Tolerance from 0° C to 70° C | | | Color Code |
|------------------------------|--|-------------|-------------|---------------|
| | ±0.2° C | ±0.5° C | ±1.0° C | |
| | Part Number | Part Number | Part Number | |
| 2,252 | ACC-001 | ACC-011 | ACC-021 | Brown |
| 3,000 | ACC-002 | ACC-012 | ACC-022 | Red |
| 5,000 | ACC-003 | ACC-013 | ACC-023 | Orange |
| 10,000 | ACC-004 | ACC-014 | ACC-024 | Yellow |
| 30,000 | ACW-005 | ACW-015 | ACW-025 | Green |
| 50,000 | ACW-006 | ACW-016 | ACW-026 | Blue |
| 100,000 | ACW-007 | ACW-017 | ACW-027 | Violet |

ACCU-CURVE™ Resistance/Temperature Table

| TEMP (°C) | "C" CURVES | | | | "W" CURVES | | |
|--------------|--------------------------|-------------------------|--------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| | 2,252 ohm s @ 25°C | 3,000 ohms @ 25°C | 5,000 ohm s @ 25°C | 10,000 ohm s @ 25°C | 30,000 ohm s @ 25°C | 50,000 ohm s @ 25°C | 100,000 ohms @ 25°C |
| -40 | 75,780 | 100,950 | 168,250 | 336,500 | 1,204,600 | 2,007,700 | 4,015,500 |
| -30 | 39,860 | 53,100 | 88,500 | 177,000 | 619,200 | 1,032,000 | 2,064,000 |
| -20 | 21,860 | 29,121 | 48,535 | 97,070 | 331,030 | 551,720 | 110,3400 |
| -10 | 12,460 | 16,599 | 27,665 | 55,330 | 183,560 | 305,940 | 611,870 |
| 0 | 7,352.8 | 9,795.0 | 16,325 | 32,650 | 105,310 | 175,510 | 351,020 |
| 10 | 4,481.5 | 5,970.0 | 9,950.0 | 19,900 | 62,354 | 103,920 | 207,850 |
| 20 | 2,812.8 | 3,747.0 | 6,245.0 | 12,490 | 38,022 | 63,370 | 126,740 |
| 25 | 2,252.0 | 3,000.0 | 5,000.0 | 10,000 | 30,000 | 50,000 | 100,000 |
| 30 | 1,814.4 | 2,417.1 | 4,028.5 | 8,057.0 | 23,827 | 39,711 | 79,422 |
| 40 | 1,199.6 | 1,598.1 | 2,663.3 | 5,327.0 | 15,314 | 25,524 | 51,048 |
| 50 | 811.40 | 1,080.9 | 1,801.5 | 3,603.0 | 10,077 | 16,795 | 33,591 |
| 60 | 560.30 | 746.40 | 1,244.0 | 2,488.0 | 6,777.1 | 11,295 | 22,590 |
| 70 | 394.55 | 525.60 | 876.00 | 1,752.0 | 4,650.5 | 7,750.9 | 15,502 |
| 80 | 282.63 | 376.50 | 627.50 | 1,255.0 | 3,251.2 | 5,418.7 | 10,837 |
| 90 | 206.13 | 274.59 | 457.65 | 915.30 | 2,312.3 | 3,853.9 | 7,707.7 |
| 100 | 152.75 | 203.49 | 339.15 | 678.30 | 1,670.8 | 2,784.6 | 5,569.3 |
| 110 | 114.92 | 153.09 | 255.15 | 510.30 | 1,224.9 | 2,041.5 | 4,082.9 |
| 120 | 87.671 | 116.79 | 194.65 | 389.30 | 909.99 | 1,516.7 | 3,033.3 |
| 130 | 67.770 | 90.279 | 150.47 | 300.93 | 684.31 | 1,140.5 | 2,281.0 |
| 140 | 52.983 | 70.581 | 117.64 | 235.27 | 520.30 | 867.16 | 1,734.3 |
| 150 | 41.881 | 55.791 | 92.985 | 185.97 | 399.56 | 665.94 | 1,331.9 |

The ACCU-CURVE™ device can also be supplied with 32 AWG solid Teflon insulated leads of 3, 6, 9 and 12 inches in length. contact Ametherm applications engineering for additional information. Warning: Use Heat sinks when soldering to Thermistor Leads.

ACCU-CURVE™ Resistance/Temperature Conversion Tables

| ACCX-0XX "C" CURVE | | ACCX-0XX "C" CURVE | | ACWX-0XX "W" CURVE | | ACWX-0XX "W" CURVE | |
|-----------------------|--------|-----------------------|--------|-----------------------|--------|-----------------------|--------|
| TEMP. °C | RT/R25 | TEMP. °C | RT/R25 | TEMP. °C | RT/R25 | TEMP. °C | RT/R25 |
| 0 | 3.265 | 36 | 0.6267 | 0 | 3.5102 | 36 | 0.6074 |
| 1 | 3.103 | 37 | 0.6017 | 1 | 3.3264 | 37 | 0.5814 |
| 2 | 2.950 | 38 | 0.5777 | 2 | 3.1532 | 38 | 0.5566 |
| 3 | 2.805 | 39 | 0.5547 | 3 | 2.9899 | 39 | 0.5330 |
| 4 | 2.669 | 40 | 0.5327 | 4 | 2.8360 | 40 | 0.5105 |
| 5 | 2.539 | 41 | 0.5117 | 5 | 2.6908 | 41 | 0.4891 |
| 6 | 2.417 | 42 | 0.4917 | 6 | 2.5539 | 42 | 0.4686 |
| 7 | 2.301 | 43 | 0.4727 | 7 | 2.4246 | 43 | 0.4492 |
| 8 | 2.192 | 44 | 0.4543 | 8 | 2.3026 | 44 | 0.4306 |
| 9 | 2.088 | 45 | 0.4370 | 9 | 2.1873 | 45 | 0.4129 |
| 10 | 1.990 | 46 | 0.4200 | 10 | 2.0785 | 46 | 0.3961 |
| 11 | 1.897 | 47 | 0.4040 | 11 | 1.9756 | 47 | 0.3800 |
| 12 | 1.809 | 48 | 0.3890 | 12 | 1.8784 | 48 | 0.3646 |
| 13 | 1.725 | 49 | 0.3743 | 13 | 1.7865 | 49 | 0.3499 |
| 14 | 1.646 | 50 | 0.3603 | 14 | 1.6995 | 50 | 0.3359 |
| 15 | 1.571 | 51 | 0.3467 | 15 | 1.6173 | 51 | 0.3225 |
| 16 | 1.500 | 52 | 0.3340 | 16 | 1.5395 | 52 | 0.3098 |
| 17 | 1.432 | 53 | 0.3217 | 17 | 1.4658 | 53 | 0.2976 |
| 18 | 1.368 | 54 | 0.3099 | 18 | 1.3961 | 54 | 0.2859 |
| 19 | 1.307 | 55 | 0.2986 | 19 | 1.3300 | 55 | 0.2748 |
| 20 | 1.249 | 56 | 0.2878 | 20 | 1.2674 | 56 | 0.2641 |
| 21 | 1.194 | 57 | 0.2774 | 21 | 1.2081 | 57 | 0.2539 |
| 22 | 1.142 | 58 | 0.2675 | 22 | 1.1519 | 58 | 0.2442 |
| 23 | 1.092 | 59 | 0.2579 | 23 | 1.0985 | 59 | 0.2348 |
| 24 | 1.045 | 60 | 0.2488 | 24 | 1.0480 | 60 | 0.2259 |
| 25 | 1.000 | 61 | 0.2400 | 25 | 1.0000 | 61 | 0.2174 |
| 26 | 0.9573 | 62 | 0.2316 | 26 | 0.9545 | 62 | 0.2092 |
| 27 | 0.9167 | 63 | 0.2235 | 27 | 0.9113 | 63 | 0.2014 |
| 28 | 0.8777 | 64 | 0.2157 | 28 | 0.8702 | 64 | 0.1939 |
| 29 | 0.8407 | 65 | 0.2083 | 29 | 0.8313 | 65 | 0.1867 |
| 30 | 0.8057 | 66 | 0.2011 | 30 | 0.7942 | 66 | 0.1798 |
| 31 | 0.7723 | 67 | 0.1942 | 31 | 0.7590 | 67 | 0.1732 |
| 32 | 0.7403 | 68 | 0.1876 | 32 | 0.7256 | 68 | 0.1669 |
| 33 | 0.7097 | 69 | 0.1813 | 33 | 0.6938 | 69 | 0.1608 |
| 34 | 0.6807 | 70 | 0.1752 | 34 | 0.6636 | 70 | 0.1550 |
| 35 | 0.6530 | | | 35 | 0.6348 | | |

To determine the nominal resistance value of a thermistor at a specified temperature, multiply its R_T/R_{25} value for the desired temperature and R-T curve from the table above by its nominal resistance at 25 °C.

More Information:

[What is an NTC thermistor? \(/thermistor/what-is-an-ntc-thermistor\)](#)