

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .


MF58 MF51




CANTHERM

Supplying high-quality bimetal and thermal sensor products.

PRECISION GLASS ENCAPSULATED
NTC THERMISTORS (MF58 & MF51)



MF58



Glass Shell Precision NTC Thermistors


The MF58 is a NTC thermistor which is manufactured using a combination of ceramic and semiconductor techniques. It is equipped with tinned axial leads and then wrapped with purified glass.

Applications

Temperature compensation and detection for:

- Household appliances (air conditioners, microwave ovens, electric fans, electric heaters etc.)
- Office equipment (copiers, printers etc.)
- Industrial, medical, environmental, weather and food processing equipment
- Liquid level detection and flow rate measurement
- Mobile phone battery
- Apparatus coils, integrated circuits, quartz crystal oscillators and thermocouples.

Dimensions (mm)




Features

- Good stability and repeatability
- High reliability
- Wide range of resistance: 0.1~1000K Ω
- Tight tolerance on resistance and Beta values
- Usable in high-temperature and high-moisture environments
- Small, light, strong package,
- Suitable for automatic insertion on thru-hole PCBs
- Rapid response
- High sensitivity


Main Techno-Parameter

- Zero power resistance range (R25): 0.1~1000K Ω
- Available tolerances of R25:
F=±1% G=±2% H=±3% J=±5% K=±10%
- B value (B25/50°C) range: 3100~4500K
- Available tolerances of B value: ±0.5%, ±1%, ±2%
- Dissipation factor: $\geq 2\text{mW}/^\circ\text{C}$ (In Still Air)
- Thermal time constant: $\leq 20\text{S}$ (In Still Air)
- Operating temperature range: $-55^\circ\text{C} \sim +200^\circ\text{C}$
- Rated Power: $\leq 50\text{mW}$

Specifications



MF51-B



Precision Glass Encapsulated NTC Thermistor for Temperature Measurement

The MF51 NTC thermistor is a small chip thermistor encased in glass with bare radial copper leads. The chip is made from a new material using new techniques which provide benefits such as high precision, fast response, reliable stability, no aging effect and improved moisture resistance.

Applications

It can be used in applications such as refrigeration, HVAC, heating equipment, electronic thermostats, liquid level sensing, automotive electronics, electronic dashboards, etc.

Dimensions (mm)



Specifications

MF51 B 103 F 3380

F = ±1%
G = ±2%
H = ±3%
J = ±5%

- The first pane holds the dimensional code.
 - The second pane shows the rated resistance at 25C (R25).
 - The third pane shows the tolerance code of rated resistance.
 - The fourth pane shows the Beta value (B25/50C)
- Type high precision temp. measurement chip in glass NTC thermistor

Note: Specifications can change without notice.

MF51 Continued >



CANTHERM

MF51-B Physical Characteristics

Model	Dissi. Coef (mW/°C)	Thermal Time Constant (S)
	In still air	In still air
MF51-B	≥ 1.0	≤ 12

Model	Rated Resistance R25		B Value (25/50°C)		Operating Temp. (°C)
	KΩ	Tolerance	K	Tolerance	
MF51B __3380	2 - 10	± 1% ± 2% ± 3% ± 5%	3380	* ± 2% ± 3%	-50°C–260°C
MF51B __3950	10 - 50		3950		
MF51B __3950	50 - 100		3950		
MF51B __4150	100 - 350		4150		

* If the tolerance of R25 is ±1%, the tolerance of B25/50 = ±1%.

If the tolerance of R25 is ±2% or greater, the tolerance of B25/50 = ±2%.



CANTHERM

Supplying high-quality bimetal and thermal sensor products.

8415 Mountain Sights Avenue • Montreal (Quebec), H4P 2B8, Canada

Tel: (514) 739-3274 • 1-800-561-7207 • Fax: (514) 739-2902 • E-mail: sales@cantherm.com

Website: www.cantherm.com | Division of Microtherm

2011/Jan MF51/MF58