

阅读申明



- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .



Agency Approvals

Agency	Agency File Number	Ampere Range
	E10480	0.5A - 30A
	LR 29862	0.5A - 30A



Description

BLF fuses offer safe and reliable protection at a low price for its size, type and features. They are suitable for control circuit and instrument protection in dry (little to no humidity) locations.


Electrical Characteristics for Series

% of Ampere Rating	Ampere Rating	Opening Time
100%	0-30	Until temp stabilizes
135%	0-30	1 hours, Maximum
200%	0-30	2 minutes, Maximum


Electrical Specifications by Item

Ordering Number	Amp Rating (A)	Max Voltage Rating (V)	Interrupting Rating	Nominal Cold Resistance (Ohms)	Agency Approvals	
						
BLF .500	.500	250	10,000 amperes at rated VAC.	1.57	x	x
BLF 001	1			.395	x	x
BLF 01.5	1.5			.2191	x	x
BLF 002	2			.125	x	x
BLF 02.5	2.5			.0946	x	x
BLF 003	3			.0696	x	x
BLF 004	4			.0432	x	x
BLF 005	5			.0413	x	x
BLF 006	6			.02842	x	x
BLF 6.25	6.25			.02741	x	x
BLF 007	7			.02282	x	x
BLF 008	8			.01664	x	x
BLF 009	9			.01364	x	x
BLF 010	10			.0117	x	x
BLF 012	12			.00920	x	x
BLF 015	15			.00920	x	x
BLF 020	20	125	.00528	x	x	
BLF 025	25		.00378	x	x	
BLF 030	30		.00289	x	x	

Temperature Derating Curve



Average Time Current Curves



Dimensions

