

## 阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

## Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

# Axial Lead and Cartridge Fuses

## Glass Body

### 3.6 x 10 mm Fast-Acting Fuse 672 Series



- Designed to UL/CSA 248 Standard.
- Fast-Acting, glass body fuse in a compact package.
- This space saving fuse is ideally suited for lighting, power supply, and adapter applications.

#### ELECTRICAL CHARACTERISTICS:

| % of Ampere Rating | Opening Time     |
|--------------------|------------------|
| 100%               | 4 hours, Minimum |
| 200%               | 5 seconds, Max.  |

**AGENCY APPROVALS:** Listed by Underwriters Laboratories and Certified by CSA from 0.050 through 10 Amps.

#### INTERRUPTING RATING:


50A@250V AC

#### PACKAGING OPTIONS:


Please refer to the following suffixes when ordering:  
 Bulk (1000 pieces): Add MXE suffix to the catalog part number.  
 Tape and Reel (1500 pieces): Add DRT4 suffix to the catalog part number.

#### TAPE AND REEL SPECIFICATIONS:

Per EIA-296 with 10mm pitch and 56.5mm inside tape spacing.



**672 000 Series**



Axial Lead Material: Solder coated copper.

#### ORDERING INFORMATION:

| Catalog Number | Ampere Rating | Voltage Rating | Nominal Resistance Cold mOhms | Nominal Melting $i^2t$ A <sup>2</sup> Sec. |
|----------------|---------------|----------------|-------------------------------|--|
| 0672.100       | .100          | 250            | 4.8250                        | 0.00194                                    |
| 0672.125       | .125          | 250            | 3.8620                        | 0.00289                                    |
| 0672.200       | .200          | 250            | 1.7302                        | 0.0114                                     |
| 0672.250       | .250          | 250            | 1.6120                        | 0.0225                                     |
| 0672.300       | .300          | 250            | 0.9250                        | 0.0295                                     |
| 0672.400       | .400          | 250            | 0.5840                        | 0.0695                                     |
| 0672.500       | .500          | 250            | 0.2322                        | 0.128                                      |
| 0672.600       | .600          | 250            | 0.1765                        | 0.218                                      |
| 0672.750       | .750          | 250            | 0.1310                        | 0.254                                      |
| 0672.800       | .800          | 250            | 0.1215                        | 0.304                                      |
| 0672 001.      | 1.00          | 250            | 0.1056                        | 0.508                                      |
| 0672 01.5      | 1.50          | 250            | 0.0595                        | 0.884                                      |
| 0672 01.6      | 1.60          | 250            | 0.0565                        | 0.965                                      |
| 0672 002.      | 2.00          | 250            | 0.0378                        | 2.27                                       |
| 0672 02.5      | 2.50          | 250            | 0.0342                        | 3.73                                       |
| 0672 3.15      | 3.15          | 250            | 0.0253                        | 5.95                                       |
| 0672 004.      | 4.00          | 250            | 0.0174                        | 8.86                                       |
| 0672 04.5      | 4.50          | 250            | 0.0170                        | 9.77                                       |
| 0672 005.      | 5.00          | 250            | 0.0145                        | 15.6                                       |
| 0672 006.      | 6.00          | 250            | 0.0132                        | 18.0                                       |
| 0672 06.3      | 6.30          | 250            | 0.0120                        | 19.3                                       |
| 0672 06.5      | 6.50          | 250            | 0.0118                        | 21.9                                       |
| 0672 007.      | 7.00          | 250            | 0.0111                        | 25.8                                       |
| 0672 008.      | 8.00          | 250            | 0.0088                        | 33.2                                       |
| 0672 010.      | 10.0          | 250            | 0.0056                        | 88.5                                       |

#### Average Time Current Curves

