

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。





Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

322/332 Series Lead-free 3AB, Very Fast-acting Fuse



Agency Approvals

| Agency | Agency File Number | Ampere Range | Series |
|---|--|---------------|---------|
|  | E10480 | 12A - 30A | 322 |
|  | E10480 | 1A - 10A | 332 |
|  | NBK080306-JP1021A NBK080306-JP1021B | 1-5A 6-10A | 332 |
|  | N/A | 1A - 30A | 322/332 |

Description

The 3AB Very Fast-Acting Fuse for protection of Silicon Controlled Rectifiers and similar solid-state devices.

Features

- In accordance with UL Standard 248-14
- Available in cartridge format only
- RoHS compliant and Lead-free





Applications

Used as supplementary protection in appliance or utilization equipment to provide individual protection for components or internal circuits.

Electrical Characteristics for Series

| % of Ampere Rating | Ampere Rating | Opening Time |
|--------------------|---------------|--------------------|
| 100% | 1 – 30 | 4 hours, Minimum |
| 250% | 1 – 10 | .2 second, Maximum |
| | 12 – 30 | 1 second, Maximum. |


Electrical Characteristic Specifications by Item

| Amp Code | Ampere Rating (A) | Voltage Rating (V) | Interrupting Rating | Nominal Cold Resistance (Ohms) | Nominal Melting I ² t (A ² sec) | Agency Approvals | | | |
|----------|-------------------|--------------------|--|--------------------------------|---|---|---|---|---|
| | | | | | |  |  |  |  |
| 001. | 1 | 250 | 100A@250Vac 100A@125Vdc 200A@72Vdc | 0.0927 | 0.146 | x | | x | x |
| 1.25 | 1.25 | 250 | | 0.0804 | 0.204 | x | | x | x |
| 002. | 2 | 250 | | 0.0416 | 0.790 | x | | x | x |
| 003. | 3 | 250 | | 0.0245 | 2.760 | x | | x | x |
| 004. | 4 | 250 | | 0.0179 | 3.360 | x | | x | x |
| 005. | 5 | 250 | | 0.0128 | 6.250 | x | | x | x |
| 006. | 6 | 250 | | 0.0117 | 8.208 | x | | x | x |
| 007. | 7 | 250 | | 0.0108 | 10.58 | x | | x | x |
| 008. | 8 | 250 | | 0.0088 | 16.45 | x | | x | x |
| 009. | 9 | 250 | | 0.0077 | 20.66 | x | | x | x |
| 010. | 10 | 250 | 0.0073 | 24.0 | x | | x | x | |
| 012. | 12 | 65 | 200A@65Vac 1000A@65Vdc | 0.0057 | 38.0 | | x | | x |
| 015. | 15 | 65 | | 0.0043 | 59.0 | | x | | x |
| 020. | 20 | 65 | | 0.0034 | 192.0 | | x | | x |
| 025.* | 25 | 65 | | 0.0029 | 325.0 | | x | | x |
| 030.* | 30 | 65 | | 0.0023 | 540.0 | | x | | x |

* Ratings from 1A to 10A are available for 332 series


* Ratings from 12A to 30A are available for 322 series, these ratings are RoHS compliant version.

Temperature Re-rating Curve



Note:
 Re-rating depicted in this curve is in addition to the industry practice derating of 25% for continuous operation.

Average Time Current Curves



Product Characteristics


| | |
|--------------------------|---|
| Materials | Body: Ceramic Cap: Nickel-plated brass |
| Terminal Strength | MIL-STD-202, Method 211, Test Condition A |
| Solderability | MIL-STD-202 Method 208 |
| Product Marking | Cap1: Brand logo, current and voltage ratings Cap2: Series and agency approval marks |

| | |
|------------------------------|--|
| Operating Temperature | -55°C to +125°C |
| Thermal Shock | MIL-STD-202, Method 107, Test Condition B: (5 cycles -65°C to +125°C) |
| Vibration | MIL-STD-202, Method 201 |
| Humidity | MIL-STD-202, Method 103, Test Condition A: High RH (95%) and Elevated temperature (40°C) for 240 hours |
| Salt Spray | MIL-STD-202, Method 101, Test Condition B |


Dimensions

Measurements displayed in millimeters (inches)

322 000P / 332 000P Series (cartridge)



Part Numbering System



Packaging

| Packaging Option | Packaging Specification | Quantity | Quantity & Packaging Code | Reel Size |
|-------------------|-------------------------|----------|---------------------------|-----------|
| 322 Series | | | | |
| Bulk | N/A | 1000 | MX | N/A |
| Bulk | N/A | 100 | HX | N/A |
| 332 Series | | | | |
| Bulk | N/A | 100 | HX | N/A |
| Bulk | N/A | 1000 | MX | N/A |

Additional Information



Datasheet
322 Series



Resources
322 Series



Samples
322 Series



Datasheet
332 Series



Resources
332 Series



Samples
332 Series



Accessories
322 & 332 Series

For recommended fuse accessories for this product series, see '[Recommended Accessories](#)' section.

Recommended Accessories

| Accessory Type | Series | Description | Max Application Voltage | Max Application Amperage |
|----------------|------------------------|---|-------------------------|--------------------------|
| Holder | 155100 | Twist-Lock In-Line Fuseholder | 32 | 20 |
| | 342 | Traditional Panel Mount Fuseholder | 250 | 20 |
| | 346 | Panel Mount Flip-Top Shock-Safe Fuseholder | 250 | 15 |
| | 345 | Shock-Safe Fuseholder with PC Mount, Solder Mount and Panel Mount options | 250 | 20 |
| Block | 354 | Low Profile OMNI-BLOK® Fuse Block | 600 | 30 |
| | 359 | High Current Screw Terminal Fuse Block | | 30 |
| Clip | 122 | High Current Traditional PC Board Fuse Clip | 1000 | 30 |
| | 101 | Rivet/Eyelet Type Fuse Clip | 1000 | 15 |

Notes:

- Do not use in applications above rating.
- Please refer to fuseholder data sheet for specific re-rating information.
- Please contact factory for applications greater than the max voltage and amperage shown.