


阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。


Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

Low Jitter and Skew DC to 220 MHz Clock Buffer

| | |
|---|---|
| <p>Key Features</p> <ul style="list-style-type: none"> • DC to 220 MHz operating frequency range • Low output clock skew: 70ps-typ • Low part-to-part output skew: 100 ps-typ • Low output propagation delay: 3.5ns-typ • 3.3V to 2.5V operation supply voltage range • Low power dissipation <ul style="list-style-type: none"> - 11 mA-typ at 66MHz at VDD=3.3V - 10 mA-typ at 66MHz at VDD=2.5V • One input to nine (9) output fanout buffer drivers • Available in 16-pin SOIC package • Available in Commercial and Industrial grades • Available in Lead (Pb) free package • <p>Applications</p> <ul style="list-style-type: none"> • General Purpose PCI/PCI-X Clock Buffer • Printers, MFPs and Digital Copiers • PCs and Work Stations • Routers, Switches and Servers • Datacom and Telecom • High-Speed Digital Embedded Systems | <p>Description</p> <p>The SL23EP09NZ is a low skew, jitter and power fanout buffer designed to produce up to nine (9) clock outputs from one (1) reference input clock, for high speed clock distribution.</p> <p>The SL23EP09NZ products operate from DC to 220MHz and within 3.3V to 2.5V power supply range.</p> <p>Refer to SL2309NZ product for DC to 140MHz-max frequency range. Also refer to SL2304NZ or SL23EP04NZ products for 1:4 clock fanout buffers within 3.3V to 2.5V power supply and DC to 220MHz frequency range.</p> <p>Benefits</p> <ul style="list-style-type: none"> • Up to nine (9) distribution of input clock • Low propagation delay • Low output-to-output skew • Low output clock jitter • Low power dissipation |
| <p>Block Diagram</p>  <p>The block diagram shows a single input pin labeled CLKIN with a square symbol containing an 'X'. This input is connected to a vertical bus that branches into nine separate signal paths. Each path contains a buffer symbol (a triangle with a dot at the input) followed by an output pin labeled OUTPUT1 through OUTPUT9, each also with a square symbol containing an 'X'. At the bottom left, there are two power pins: VDD(3) and GND(3), each with a square symbol containing an 'X'.</p> | |

Pin Configuration



16-Pin SOIC

Pin Description

| Pin Number | Pin Name | Pin Type | Pin Description |
|------------|----------|----------|-----------------------------------|
| 1 | CLKIN | Input | Input Reference Clock |
| 2 | OUTPUT1 | Output | Buffered Clock Output-1 |
| 3 | OUTPUT2 | Output | Buffered Clock Output-2 |
| 4 | VDD | Power | 3.3V +/-10% Power Supply |
| 5 | GND | Power | Power Ground |
| 6 | OUTPUT3 | Output | Buffered Clock Output-3 |
| 7 | OUTPUT4 | Output | Buffered Clock Output-4 |
| 8 | VDD | Power | 3.3V and 2.5V +/-10% Power Supply |
| 9 | GND | Power | Power Ground |
| 10 | OUTPUT5 | Output | Buffered Clock Output-5 |
| 11 | OUTPUT6 | Output | Buffered Clock Output-6 |
| 12 | GND | Power | Power Ground |
| 13 | VDD | Power | 3.3V and 2.5V +/-10% Power Supply |
| 14 | OUTPUT7 | Output | Buffered Clock Output-7 |
| 15 | OUTPUT8 | Output | Buffered Clock Output-8 |
| 16 | OUTPUT9 | Output | Buffered Clock Output-9 |

General Description

The SL23EP09NZ is a low skew, jitter and power fanout buffer designed to produce up to nine (9) clock outputs from one (1) reference input clock, for high speed clock distribution, including PCI/PCI-X applications.

Input and output Frequency Range

The input and output frequency is the same (1x) for SL2309NZ and the product operates from DC to 220MHz clock range with 15pF and 134MHz with 30pF output loads at VDD=3.3V.

High Drive Capability

The SL23EP09NZ is designed to meet high drive requirements for up to 30pF load condition per electrical specifications tables.

If lower drive levels are required refer to SL2309NZ fanout buffer product.

Output Clock Skew

All outputs should drive the similar load to achieve output-to-output skew specifications as given in the switching electrical tables.

Power Supply Range (VDD)

The SL23EP09NZ is designed to operate from 3.3V to 2.5V VDD power supply range. An internal on-chip voltage regulator is used to provide to constant power supply of 1.8V, leading to a consistent and stable electrical performance in terms of skew and jitter. The SL23EP09NZ I/O is powered by using VDD.

Refer to SL2309NZ product for DC to 140MHz-max frequency range.

Contact SLI for 1.8V power supply Buffers and ZDB products.

Absolute Maximum Ratings (C-Grade and I-Grade)

| Description | Condition | Min | Max | Unit |
|----------------------------------|--------------------------------|--------|---------|------|
| Supply voltage, VDD | | -0.5 | 4.2 | V |
| All Inputs and Outputs | | -0.5 | VDD+0.5 | V |
| Ambient Operating Temperature | In operation, C-Grade | 0 | 70 | °C |
| Ambient Operating Temperature | In operation, I-Grade | -40 | 85 | °C |
| Storage Temperature | No power is applied | -65 | 150 | °C |
| Junction Temperature | In operation, power is applied | – | 125 | °C |
| Soldering Temperature | | – | 260 | °C |
| ESD Rating (Human Body Model) | JEDEC22-A114D | -4,000 | 4,000 | V |
| ESD Rating (Charge Device Model) | JEDEC22-C101C | -1,500 | 1,500 | V |
| ESD Rating (Machine Model) | JEDEC22-A115D | -200 | 200 | V |

Operating Conditions (C-Grade and I-Grade)

Unless otherwise stated VDD= 3.3V+/- 10%, CL=15pF

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|-----------------------|--------|--------------------------------|------|-----|------|------|
| Operating Voltage | VDD | VDD+/-10% | 2.97 | 3.3 | 3.63 | V |
| Operating Temperature | TA1 | Ambient Temperature C-Grade | 0 | – | 70 | °C |
| | TA2 | Ambient Temperature I-Grade | -40 | – | 85 | °C |
| Input Capacitance | VINC | Pin 1 | – | 5 | 7 | pF |
| Load Capacitance | CL1 | All outputs ≤ 220MHz, 3.3V | – | – | 15 | pF |
| | CL2 | All outputs ≤ 134MHz, 3.3V | – | – | 30 | pF |
| Operating Frequency | CLKIN | Input Clock Range, CL=15pF | DC | – | 220 | MHz |
| Operating Frequency | CLKIN | Input Clock Range, CL=30pF | DC | – | 134 | MHz |

DC Electrical Characteristics (C-Grade)

Unless otherwise stated VDD= 3.3V+/- 10%, CL=15pF and Ambient Temperature range 0 to +70°C

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|----------------------|--------|---------------------|-----|-----|---------|------|
| Input LOW Voltage | VINL | CLKIN | – | – | 0.8 | V |
| Input HIGH Voltage | VINH | CLKIN | 2.0 | – | VDD+0.3 | V |
| Input LOW Current | IINL | 0 < VIN < 0.8V | – | – | 10 | µA |
| Input HIGH Current | IINH | 2.4V < VIN < VDD | – | – | 15 | µA |
| Output Low Voltage | VOL | IoL=12mA | – | – | 0.4 | V |
| Output High Voltage | VOH | IoH=-12mA | 2.4 | – | – | V |
| Power Supply Current | IDD1 | CLKIN=33.3MHz, CL=0 | – | 9 | 13 | mA |
| Power Supply Current | IDD2 | CLKIN=66.6MHz, CL=0 | – | 11 | 16 | mA |
| Power Supply Current | IDD3 | CLKIN=166MHz, CL=0 | – | 15 | 20 | mA |

Switching Electrical Characteristics (C-Grade)

Unless otherwise stated VDD= 3.3V+/- 10%, CL=15pF and Ambient Temperature range 0 to +70°C

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|------------------------|--------|---|-----|-----|-----|------|
| Output Frequency Range | FOUT1 | CL=15pf | 0 | – | 220 | MHz |
| | FOUT2 | CL=30pf | 0 | – | 134 | MHz |
| Input Duty Cycle | DC1 | Measured at VDD/2 | 20 | 50 | 80 | % |
| Output Duty Cycle | DC2 | CL=15pF, Fout=166MHz Measured at VDD/2 | 45 | 50 | 55 | % |
| Output Duty Cycle | DC3 | CL=30pF, Fout=100MHz Measured at VDD/2 | 40 | 50 | 60 | % |
| Output Rise/Fall Time | tr/f-1 | Measured at 0.8V to 2.0V | – | – | 1.2 | ns |

| | | CL=15pF | | | | |
|------------------------|--------|---|-----|-----|-----|----|
| Output Rise/Fall Time | tr/f-2 | Measured at 0.8V to 2.0V CL=30pF | - | - | 1.6 | ns |
| Output Skew | SKW1 | Measured at VDD/2 and Outputs are equally loaded | - | 70 | 150 | ps |
| Part to Part Skew | SKW2 | Measured at VDD/2 and Outputs are equally loaded | - | 100 | 200 | ps |
| Propagation Delay Time | PDT | Measured at VDD/2 from CLKIN to Output Clock rising edge and Outputs are equally loaded | 2.5 | 3.5 | 4.5 | ns |
| Cycle-to-Cycle Jitter | CCJ1 | CLKIN=66MHz and CL=0 (No Load) | - | 35 | 70 | ps |
| Cycle-to-Cycle Jitter | CCJ2 | CLKIN=166MHz and CL=0 (No Load) | - | 25 | 50 | ps |

DC Electrical Characteristics (I-Grade)

Unless otherwise stated VDD= 3.3V+/- 10%, CL=15pF and Ambient Temperature range -40 to +85°C

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|----------------------|--------|----------------------|-----|-----|---------|------|
| Input LOW Voltage | VINL | CLKIN | - | - | 0.8 | V |
| Input HIGH Voltage | VINH | CLKIN | 2.0 | - | VDD+0.3 | V |
| Input LOW Current | IINL | 0 < VIN < 0.8V | - | - | 10 | µA |
| Input HIGH Current | IINH | 2.4V < VIN < VDD | - | - | 15 | µA |
| Output Low Voltage | VOL | IOL=12mA | - | - | 0.4 | V |
| Output High Voltage | VOH | IOH=-12mA | 2.4 | - | - | V |
| Power Supply Current | IDD1 | CLKIN=33.3MHz, CL=0 | - | 10 | 14 | mA |
| Power Supply Current | IDD2 | CLKIN=66.6MHz, CL=0 | - | 12 | 17 | mA |
| Power Supply Current | IDD3 | CLKIN=133.3MHz, CL=0 | - | 16 | 21 | mA |

Switching Electrical Characteristics (I-Grade)

Unless otherwise stated VDD= 3.3V+/- 10%, CL=15pF and Ambient Temperature range -40 to +85°C

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|------------------------|--------|---|-----|-----|-----|------|
| Output Frequency Range | FOUT1 | CL=15pf | 0 | - | 220 | MHz |
| | FOUT2 | CL=30pf | 0 | - | 134 | MHz |
| Input Duty Cycle | DC1 | Measured at VDD/2 | 20 | 50 | 80 | % |
| Output Duty Cycle | DC2 | CL=15pF, Fout=166MHz Measured at VDD/2 | 45 | 50 | 55 | % |
| Output Duty Cycle | DC3 | CL=30pF, Fout=100MHz Measured at VDD/2 | 40 | 50 | 60 | % |
| Output Rise/Fall Time | tr/f-1 | Measured at 0.8V to 2.0V, CL=15pF | - | - | 1.4 | ns |
| Output Rise/Fall Time | tr/f-2 | Measured at 0.8V to 2.0V, CL=30pF | - | - | 1.8 | ns |

| | | | | | | |
|------------------------|------|---|-----|-----|-----|----|
| Output Skew | SKW1 | Measured at VDD/2 and Outputs are equally loaded | – | 80 | 160 | ps |
| Part to Part Skew | SKW2 | Measured at VDD/2 and Outputs are equally loaded | – | 110 | 220 | ps |
| Propagation Delay Time | PDT | Measured at VDD/2 from CLKIN to Output Clock rising edge and Outputs are equally loaded | 2.0 | 3.5 | 4.8 | ns |
| Cycle-to-Cycle Jitter | CCJ1 | CLKIN=66MHz and CL=0 (No Load) | – | 40 | 80 | ps |
| Cycle-to-Cycle Jitter | CCJ2 | CLKIN=133MHz and CL=0 (No Load) | – | 30 | 60 | ps |

Operating Conditions (C-Grade and I-Grade)

Unless otherwise stated VDD= 2.5V+/- 10%, CL=15pF

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|-----------------------|---------|-----------------------------|------|-----|------|------|
| Operating Voltage | VDD | VDD+/-10% | 2.25 | 2.5 | 2.75 | V |
| Operating Temperature | TA1 | Ambient Temperature C-Grade | 0 | – | 70 | °C |
| | TA2 | Ambient Temperature I-Grade | -40 | – | 85 | °C |
| Input Capacitance | VINC | Pin 1 | – | 5 | 7 | pF |
| Load Capacitance | CL1 | All outputs ≤180MHz | – | – | 15 | pF |
| | CL2 | All outputs ≤100MHz | – | – | 30 | pF |
| Operating Frequency | CLKIN-1 | Input Clock Range, CL=15pF | DC | – | 180 | MHz |
| Operating Frequency | CLKIN-2 | Input Clock Range, CL=30pF | DC | – | 80 | MHz |

DC Electrical Characteristics (C-Grade)

Unless otherwise stated VDD= 2.5V+/- 10%, CL=15pF and Ambient Temperature range 0 to +70°C

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|----------------------|--------|---------------------|---------|-----|---------|------|
| Input LOW Voltage | VINL | CLKIN | – | – | 0.7 | V |
| Input HIGH Voltage | VINH | CLKIN | 1.7 | – | VDD+0.3 | V |
| Input LOW Current | IINL | 0 < VIN < 0.8V | – | – | 15 | µA |
| Input HIGH Current | IINH | 2.4V < VIN < VDD | – | – | 25 | µA |
| Output Low Voltage | VOL | IoL=8mA | – | – | 0.4 | V |
| Output High Voltage | VOH | IoH=–8mA | VDD-0.6 | – | – | V |
| Power Supply Current | IDD1 | CLKIN=33.3MHz, CL=0 | – | 9 | 14 | mA |
| Power Supply Current | IDD2 | CLKIN=66MHz, CL=0 | – | 11 | 17 | mA |
| Power Supply Current | IDD3 | CLKIN=166MHz, CL=0 | – | 15 | 21 | mA |

Switching Electrical Characteristics (C-Grade)

Unless otherwise stated VDD= 2.5V+/- 10%, CL=15pF and Ambient Temperature range 0 to +70°C

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|------------------------|--------|---|-----|-----|-----|------|
| Output Frequency Range | FOUT1 | CL=15pf | 0 | – | 180 | MHz |
| | FOUT2 | CL=30pf | 0 | – | 80 | MHz |
| Input Duty Cycle | DC1 | Measured at VDD/2 | 20 | 50 | 80 | % |
| Output Duty Cycle | DC2 | CL=15pF, Fout=166MHz Measured at VDD/2 | 45 | 50 | 55 | % |
| Output Duty Cycle | DC3 | CL=30pF, Fout=80MHz Measured at VDD/2 | 40 | 50 | 60 | % |
| Output Rise/Fall Time | tr/f-1 | Measured at 0.6V to 1.8V CL=15pF | – | – | 1.6 | ns |
| Output Rise/Fall Time | tr/f-2 | Measured at 0.6V to 1.8V CL=30pF | – | – | 2.0 | ns |
| Output Skew | SKW1 | Measured at VDD/2 and Outputs are equally loaded | – | 90 | 180 | ps |
| Part to Part Skew | SKW2 | Measured at VDD/2 and Outputs are equally loaded | – | 120 | 240 | ps |
| Propagation Delay Time | PDT | Measured at VDD/2 from CLKIN to Output Clock rising edge and Outputs are equally loaded | 3.0 | 4.0 | 5.0 | ns |
| Cycle-to-Cycle Jitter | CCJ1 | CLKIN=66MHz and CL=0 (No Load) | – | 50 | 100 | ps |
| Cycle-to-Cycle Jitter | CCJ2 | CLKIN=166MHz and CL=0 (No Load) | – | 35 | 70 | ps |

DC Electrical Characteristics (I-Grade)

Unless otherwise stated VDD= 2.5V+/- 10%, CL=15pF and Ambient Temperature range -40 to +85°C

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|----------------------|--------|----------------------|---------|-----|---------|------|
| Input LOW Voltage | VINL | CLKIN | – | – | 0.7 | V |
| Input HIGH Voltage | VINH | CLKIN | 1.7 | – | VDD+0.3 | V |
| Input LOW Current | IINL | 0 < VIN < 0.8V | – | – | 15 | µA |
| Input HIGH Current | IINH | 2.4V < VIN < VDD | – | – | 25 | µA |
| Output Low Voltage | VOL | IoL=8mA | – | – | 0.4 | V |
| Output High Voltage | VOH | IoH=-8mA | VDD-0.6 | – | – | V |
| Power Supply Current | IDD1 | CLKIN=33.3MHz, CL=0 | – | 10 | 14 | mA |
| Power Supply Current | IDD2 | CLKIN=66.6MHz, CL=0 | – | 12 | 17 | mA |
| Power Supply Current | IDD3 | CLKIN=133.3MHz, CL=0 | – | 16 | 23 | mA |


Switching Electrical Characteristics (I-Grade)

Unless otherwise stated VDD= 2.5V+/- 10%, CL=15pF and Ambient Temperature range -40 to +85°C

| Description | Symbol | Condition | Min | Typ | Max | Unit |
|------------------------|--------|---|-----|-----|-----|------|
| Output Frequency Range | FOUT1 | CL=15pf | 0 | – | 180 | MHz |
| | FOUT2 | CL=30pf | 0 | – | 80 | MHz |
| Input Duty Cycle | DC1 | Measured at VDD/2 | 20 | 50 | 80 | % |
| Output Duty Cycle | DC2 | CL=15pF, Fout=166MHz Measured at VDD/2 | 45 | 50 | 55 | % |
| Output Duty Cycle | DC3 | CL=30pF, Fout=100MHz Measured at VDD/2 | 40 | 50 | 60 | % |
| Output Rise/Fall Time | tr/f-1 | Measured at 0.8V to 2.0V CL=15pF | – | – | 1.8 | ns |
| Output Rise/Fall Time | tr/f-2 | Measured at 0.8V to 2.0V CL=30pF | – | – | 2.2 | ns |
| Output Skew | SKW1 | Measured at VDD/2 and Outputs are equally loaded | – | 100 | 200 | ps |
| Part to Part Skew | SKW2 | Measured at VDD/2 and Outputs are equally loaded | – | 140 | 280 | ps |
| Propagation Delay Time | PDT | Measured at VDD/2 from CLKIN to Output Clock rising edge and Outputs are equally loaded | 2.5 | 4.0 | 5.5 | ns |
| Cycle-to-Cycle Jitter | CCJ1 | CLKIN=66MHz and CL=0 (No Load) | – | 60 | 120 | ps |
| Cycle-to-Cycle Jitter | CCJ2 | CLKIN=133MHz and CL=0 (No Load) | – | 50 | 100 | ps |

External Components & Design Considerations

Typical Application Schematic




Comments and Recommendations

Decoupling Capacitor: A decoupling capacitor of 0.1µF must be used between all VDD and VSS pins. Place the capacitor on the component side of the PCB as close to the VDD pin as possible. The PCB trace to the VDD pin and to the GND via should be kept as short as possible. Do not use vias between the decoupling capacitor and the VDD pin.

Series Termination Resistor: A series termination resistor is recommended if the distance between the output clocks and the load is over 1 ½ inch. Place the series termination resistors as close to the clock outputs as possible.

Package Outline and Package Dimensions

16-Lead SOIC (150-Mil)



Thermal Characteristics

| Parameter | Symbol | Condition | Min | Typ | Max | Unit |
|--|---------------|-------------------------|-----|-----|-----|------|
| Thermal Resistance Junction to Ambient | θ_{JA} | Still air | - | 78 | - | °C/W |
| | θ_{JA} | 1m/s air flow | - | 74 | - | °C/W |
| | θ_{JA} | 3m/s air flow | - | 70 | - | °C/W |
| Thermal Resistance Junction to Case | θ_{JC} | Independent of air flow | - | 44 | - | °C/W |

Ordering Information [1]

| Ordering Number | Marking | Shipping Package | Package | Temperature |
|------------------|-----------------|------------------|-------------|-------------|
| SL23EP09NZSC-1H | SL23EP09NZSC-1H | Tube | 16-pin SOIC | 0 to 70°C |
| SL23EP09NZSC-1HT | SL23EP09NZSC-1H | Tape and Reel | 16-pin SOIC | 0 to 70°C |
| SL23EP09NZSI-1H | SL23EP09NZSI-1H | Tube | 16-pin SOIC | -40 to 85°C |
| SL23EP09NZSI-1HT | SL23EP09NZSI-1H | Tape and Reel | 16-pin SOIC | -40 to 85°C |

Notes:

1. The SL23EP09NZ products are RoHS compliant.

The information in this document is believed to be accurate in all respects at the time of publication but is subject to change without notice. Silicon Laboratories assumes no responsibility for errors and omissions, and disclaims responsibility for any consequences resulting from the use of information included herein. Additionally, Silicon Laboratories assumes no responsibility for the functioning of undescribed features or parameters. Silicon Laboratories reserves the right to make changes without further notice. Silicon Laboratories makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Silicon Laboratories assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Silicon Laboratories products are not designed, intended, or authorized for use in applications intended to support or sustain life, or for any other application in which the failure of the Silicon Laboratories product could create a situation where personal injury or death may occur. Should Buyer purchase or use Silicon Laboratories products for any such unintended or unauthorized application, Buyer shall indemnify and hold Silicon Laboratories harmless against all claims and damages.



ClockBuilder Pro

One-click access to Timing tools, documentation, software, source code libraries & more. Available for Windows and iOS (CBGo only).

www.silabs.com/CBPro



Timing Portfolio
www.silabs.com/timing



SW/HW
www.silabs.com/CBPro



Quality
www.silabs.com/quality



Support and Community
community.silabs.com

Disclaimer

Silicon Laboratories intends to provide customers with the latest, accurate, and in-depth documentation of all peripherals and modules available for system and software implementers using or intending to use the Silicon Laboratories products. Characterization data, available modules and peripherals, memory sizes and memory addresses refer to each specific device, and "Typical" parameters provided can and do vary in different applications. Application examples described herein are for illustrative purposes only. Silicon Laboratories reserves the right to make changes without further notice and limitation to product information, specifications, and descriptions herein, and does not give warranties as to the accuracy or completeness of the included information. Silicon Laboratories shall have no liability for the consequences of use of the information supplied herein. This document does not imply or express copyright licenses granted hereunder to design or fabricate any integrated circuits. The products are not designed or authorized to be used within any Life Support System without the specific written consent of Silicon Laboratories. A "Life Support System" is any product or system intended to support or sustain life and/or health, which, if it fails, can be reasonably expected to result in significant personal injury or death. Silicon Laboratories products are not designed or authorized for military applications. Silicon Laboratories products shall under no circumstances be used in weapons of mass destruction including (but not limited to) nuclear, biological or chemical weapons, or missiles capable of delivering such weapons.

Trademark Information

Silicon Laboratories Inc.®, Silicon Laboratories®, Silicon Labs®, SiLabs® and the Silicon Labs logo®, Bluegiga®, Bluegiga Logo®, Clockbuilder®, CMEMS®, DSPLL®, EFM®, EFM32®, EFR®, Ember®, Energy Micro, Energy Micro logo and combinations thereof, "the world's most energy friendly microcontrollers", Ember®, EZLink®, EZRadio®, EZRadioPRO®, Gecko®, ISOModem®, Precision32®, ProSLIC®, Simplicity Studio®, SiPHY®, Telegesis, the Telegesis Logo®, USBXpress® and others are trademarks or registered trademarks of Silicon Laboratories Inc. ARM, CORTEX, Cortex-M3 and THUMB are trademarks or registered trademarks of ARM Holdings. Keil is a registered trademark of ARM Limited. All other products or brand names mentioned herein are trademarks of their respective holders.



Silicon Laboratories Inc.
400 West Cesar Chavez
Austin, TX 78701
USA

<http://www.silabs.com>