

阅读申明

- 1.本站收集的数据手册和产品资料都来自互联网，版权归原作者所有。如读者和版权方有任何异议请及时告之，我们将妥善解决。
- 2.本站提供的中文数据手册是英文数据手册的中文翻译，其目的是协助用户阅读，该译文无法自动跟随原稿更新，同时也可能存在翻译上的不当。建议读者以英文原稿为参考以便获得更精准的信息。
- 3.本站提供的产品资料，来自厂商的技术支持或者使用者的心得体会等，其内容可能存在描述上的差异，建议读者做出适当判断。
- 4.如需与我们联系，请发邮件到marketing@iczoom.com，主题请标有“数据手册”字样。

Read Statement

1. The datasheets and other product information on the site are all from network reference or other public materials, and the copyright belongs to the original author and original published source. If readers and copyright owners have any objections, please contact us and we will deal with it in a timely manner.
2. The Chinese datasheets provided on the website is a Chinese translation of the English datasheets. Its purpose is for reader's learning exchange only and do not involve commercial purposes. The translation cannot be automatically updated with the original manuscript, and there may also be improper translations. Readers are advised to use the English manuscript as a reference for more accurate information.
3. All product information provided on the website refer to solutions from manufacturers' technical support or users the contents may have differences in description, and readers are advised to take the original article as the standard.
4. If you have any questions, please contact us at marketing@iczoom.com and mark the subject with "Datasheets" .

eCM-BF561

Blackfin® Core Module

Core Module eCM-BF561

The Core Module eCM-BF561 is optimized for performance and parallel data processing. The module integrates processor, RAM, flash and power supply at a size of 44x33mm! It is based on the high performance ADSP-BF561 from Analog Devices. The eCM-BF561 is designed for commercial applications (commercial temperature range). It addresses 128MByte SDRAM via its 32bit wide SDRAM bus and has an onboard NOR-flash of 32MByte.

Technical Details of eCM-BF561

PROCESSOR	ADSP-BF561SKBCZ-6A Blackfin® embedded processor (Dual Core)
CLOCK	2 x 600MHz
L1 cache (per core)	16kByte instruction and 32kByte data
L2 cache (shared)	128kByte
RAM	128MByte SDRAM up to 133Mhz
FLASH	32MByte NOR
PPI 16Bit	2
SPI	1
I²C	Emulated by GPIO
UART	1
SPI	2
TEMPERATURE RANGE*	Commercial (0°C to +70°C) Industrial (-40 to +85°C)
DIMENSIONS	44x33mm
Additional	On-Board core voltage regulator Low voltage reset circuit


*depends on version - see ordering information

Operating Systems

- » BLACKSheep® OS (RTOS)
- » uClinux (GPOS)

Ordering Information

Order No.	Info
100-1214-1	eCM-BF561-C-C-Q25S128F32 (eCM-BF561)
100-1215-1	eCM-BF561-C-I-Q25S128F32
100-2342-2	eDEV-BF5xx Enhanced Blackfin Development Board
100-3400	Blackfin Evaluation Starter Package with eCM-BF561
100-3106	CDK - Camera Development Kit with eCM-BF561



eCM-BF561

Applications

- » Parallel digital signal processing
- » Automotive vision systems
- » Imaging and consumer multimedia
- » Set top boxes
- » Video conference applications
- » Portable media players
- » Digital video camera systems



eCM-BF561 also available as Camera-Development-Kit (CDK)

BLUETECHNIX MECHATRONISCHE SYSTEME GMBH

Waidhausenstrasse 3/19
1140 Wien, Austria
www.bluetechnix.com

Tel.: +43 (1) 9142091 x 0
Fax.: +43 (1) 9142091 x 99
Email: office@bluetechnix.at

